



SCRUBBER DRIERS - WALK BEHIND

CT55

MAX PRODUCTIVITY

2700 m²/h

BATTERIES
RUNNING TIME

2,5 h

WATER TANK
RUNNING TIME

60'
working session



DOUBLE BRUSH VERSION



ROLLER VERSION



BATTERIES AND BATTERY CHARGER NOT INCLUDED

MOST FREQUENTLY USE



INNOVATIONS



DBL™
DOUBLE
BATTERY
LIFE



SLS™
SELF
LEVELING
SYSTEM



BACTERIA
CONTROL

SPECS



INTUITIVE CONTROL PANEL



SEPARATE DETERGENT
DOSING SYSTEM. (OPTIONAL)



ANTI-FOAM SYSTEM WITH
SPECIAL ELECTROMECHANICAL
SUCTION MOTOR PROTECTION

TECHNICAL DATA

		CT55 B55	CT55 BT55	CT55 C55	CT55 BT60	CT55 BT55 R
Code		LPTB01516	LPTB01517	LPTB01102	LPTB01518	LPTB01519
PERFORMANCE						
Max theoretical productivity	m ² /h	1925	2475	1925	2700	2475
Cleaning path	mm	550	550	550	600	550
Water tank capacity (solution recovery)	l	55/60	55/60	55/60	55/60	55/60
Max running time	min	140	140	Unlimited	140	140
Voltage	V-Ah	24(2x12)-105 GEL	24(2x12)-105 GEL	230-50	24(2x12)-105 GEL	24(2x12)-105 GEL
Installed power	W	480	480	550	480	480
Brush pressure	kg	27	23	30	30	13,6/18,6
Squeegee width	mm	815	815	815	815	815
Max speed	km/h	3,5	4,5	4,5	4,5	4,5
Weight	kg	68	83,5	91	89,5	96
Dimension (LxWxH)	mm	1190x685x1018	1190x685x1018	1190x640x1018	1190x685x1018	1190x685x1018

STANDARD EQUIPMENT

	CT55 B55	CT55 BT55	CT55 C55	CT55 BT60	CT55 BT55 R
BRUSHES					
PPL SOFT	SPPV01505	SPPV01505	SPPV01505	2xSPPV01473	-
CYLINDRICAL BRUSH - PPL SOFT Ø 0,3 mm	-	-	-	-	SPPV01163
SQUEEGEE BLADES					
LATEX FRONT BLADE	MPVR08039 - 880mm	MPVR08039 - 880mm	MPVR08039 - 880mm	MPVR08039 - 880mm	MPVR08039 - 880mm
LATEX REAR BLADE	MPVR08035 - 900mm	MPVR08035 - 900mm	MPVR08035 - 900mm	MPVR08035 - 900mm	MPVR08035 - 900mm

CONSUMABLES (Codes available on price list)

BRUSHES



CYLINDRICAL BRUSHES



PADS/SUPER PADS



SQUEEGEE BLADES



OPTIONAL ACCESSORIES

CODE: KTRI02141
CHEM DOSE KIT



CODE: MPVR05611
SPLASH GUARD



CODE: KTRI01573
DISCHARGE HOSE



CODE: KTRI01870
SOLUTION TANK DRAIN
AND LEVEL HOSE KIT



CODE: KTRI02257
EXTERNAL SUCTION KIT



CODE: PRCH00578
BIOSAN RAPIDE WT
(30PCS/30DAYS)



BATTERIES AND BATTERY CHARGERS

BATTERIES	N°	CHARACTERISTICS	DIMENSION	RUNNING TIME	BATTERY CHARGERS
IPC gel battery BAAC00105	2	12V 105 Ah [C5]	345x170x285	150 min	On board battery charger 24V 10 Ah- KTRI01703 Stand alone high frequency BLS010 - BACA00133
EXIDE gel battery BAAC00024	2	12V 105 Ah [C5]	345x174x283	150 min	On board battery charger 24V 10 Ah- KTRI01703 Stand alone high frequency BLS010 - BACA00133
Acid tubular plate BAAC00136	2	12V 85 Ah [C5]	308x175x225	160 min	On board battery charger 24V 10 Ah- KTRI01703 Stand alone high frequency BLS010 - BACA00133 Stand alone low frequency 24V 12 Ah BACA00060
Dry charge flate plate BAAC00009	2	12V 105 Ah [C5]	261x171x210	160 min	On board battery charger 24V 10 Ah- KTRI01703 Stand alone high frequency BLS010 - BACA00133 Stand alone low frequency 24V 12 Ah BACA00060
Acid tubular plate BAAC00070	2	12V 118 Ah [C5]	345x170x285	160 min	On board battery charger 24V 10 Ah- KTRI01703 Stand alone high frequency BLS010 - BACA00133 Stand alone low frequency 24V 12 Ah BACA00060

RECOMMENDED BATTERIES AND BATTERY CHARGERS