



SWEEPERS - RIDE ON

# 1450

MAX PRODUCTIVITY

8760 m<sup>2</sup>/h

MAIN BRUSH PATH

800 mm

VOLTAGE SYSTEM

12-24 v



MOST FREQUENTLY USE



SPECS



HOPPER PNEUMATIC DISCARGHE SYSTEM



PLEATED FILTER



BATTERY BOX

## TECHNICAL DATA

		1450 E	1450 DL	1450 DY
Code		MSUB00418	MSUB00416	MSUB00417
<b>PERFORMANCE</b>				
Main brush cleaning path width	mm	800	800	800
Side brush cleaning path width	mm	1460	1460	1460
Max theoretical productivity	m <sup>2</sup> /h	8760 m <sup>2</sup> /h	8760 m <sup>2</sup> /h	8760 m <sup>2</sup> /h
Voltage	V-Ah	24	12	12
Installed power	W /HP	4000 W	5700 W	7200 W
Hopper capacity	l	150	150	150
Hopper Discharge System	Type/mm	Hydraulic -1430	Hydraulic -1430	Hydraulic -1430
Filtering surface	m <sup>2</sup>	3,1	3,1	3,1
Fylter type		Pleated	Pleated	Pleated
Max speed	km/h	6	6	6
Max Climb	%	16	20	20
Weight whitout batteries	kg	540	605	613
Dimension (LxWxH)	mm	1600x1199x1360	1600x1199x1360	1600x1199x1360

## STANDARD ACCESSORIES

		1450 E	1450 DL	1450 DY
<b>BRUSHES</b>				
MAIN BRUSH		SPPV01229	SPPV01229	SPPV01229
SIDE BRUSH		SPPV01232	SPPV01232	SPPV01232
<b>FILTERS</b>				
FILTER		FTDP00204	FTDP00204	FTDP00204

## OPTIONAL ACCESSORIES

CODE: KTRI00101

### OVERHEAD GUARD KIT



## BATTERIES AND BATTERY CHARGERS

BATTERIES	N°	CHARACTERISTIC	DIMENSION	RUNNING TIME	BATTERY CHARGERS
Acid tubolar plate battery BAAC00109	1	24V 480Ah (C5)	950x420x395	160	Stand alone low frequency 24V 60 Ah - BACA00137

RECOMMENDED BATTERIES AND BATTERY CHARGERS

IP Cleaning S.p.A.

Viale Treviso 63 - 30026 Summaga di Portogruaro (VE) - Italy  
Tel. +39 0421 205511 - Fax +39 0421 204227 - info@ipcworldwide.com - www.ipcworldwide.com



Information about watertight and airflow refers to single motors.  
Specifications, descriptions and pictures are supplied as indicative: rights to technical modifications reserved without prior notice.