



HIGH-PRESSURE WASHERS - COLD WATER

BENZ-C

PRESSURE

180÷250
bar

FLOW RATE

660÷1260
l/h

ENGINE POWER

6,5÷13
Hp



EXCLUSIVE CHARACTERISTICS

- ▶ THERMOSTATIC VALVE - TSV
- ▶ ENGINE THROTTLE CONTROL (DL MODELS) - RS

PETROL MOTORS, HONDA GX SERIES, AIR-COOLED DL MOTDELS ARE EQUIPPED WITH HYDRAULIC DECELERATOR

MOST FREQUENTLY USE



INNOVATIONS



SPECS



"L" VERSIONS ARE PROVIDED WITH A REDUCTION GEAR IN ORDER TO GUARANTEE PUMP LIFESPAN EXTENSION



FLEXIBLE COUPLING BETWEEN PUMP AND ENGINE FOR COMPONENTS LIFESPAN EXTENSION ("H" VERSION)



THERMOSTATIC VALVE PROTECTING THE PUMP FROM POSSIBLE OVERHEATING IN BY-PASS PHASE

TECHNICAL DATA

		BENZ-C H1811P	BENZ-C H2013PI P	BENZ-C H2515PI P	BENZ-C DL2515PI P	BENZ-C L2216PI P	BENZ-C L2021PI P	BENZ-C DL2217PI P	BENZ-C DL2021PI P
Code		IDAF40352	IDAF40353	IDAF40354	IDAF40355	IDAF40356	IDAF40357	IDAF40358	IDAF40359
PERFORMANCE									
Operating pressure max	bar/Mpa	30-180/3-18	30-200/3-20	30-250/3-25	30-250/3-25	30-220/3-22	30-200/3-20	30-220/3-22	30-200/3-20
Flow rate	l/h	330-660	400-800	450-900	450-900	500-1000	400-1260	450-1000	450-1260
Max inlet water temperature	°C	50	50	50	50	50	50	50	50
Engine type		Honda GX200 (gasoline)	Honda GX270 (gasoline)	Honda GX390 (gasoline)	Honda GX390 (gasoline)	Honda GX390 (gasoline)	Honda GX390 (gasoline)	Honda GX390 (gasoline)	Honda GX390 (gasoline)
Engine power	Hp	6,5	9	13	13	13	13	13	13
Engine speed	rpm	3600	3600	3600	3600	1500	1500	1500	1500
Remote control		BYP	BYP	BYP	BYP	BYP	BYP	BYP	BYP
Pump/head/pistons		IPG plunger/brass/ceramic	IPG plunger/brass/ceramic	IPG plunger/brass/ceramic	IPG plunger/brass/ceramic	IPG plunger/brass/ceramic	IPG plunger/brass/ceramic	IPG plunger/brass/ceramic	IPG plunger/brass/ceramic
Detergent tank	l	-	-	-	-	-	-	-	-
Detergent delivery		low pressure	low pressure	low pressure	low pressure	low pressure	low pressure	low pressure	low pressure
Dimension (LxWxH)	Cm	86x56x54	105x66x75	105x66x75	105x66x75	105x66x75	105x66x75	105x66x75	105x66x75
Weight	Kg	47	70	75	75	85	85	75	75
Motor-pump coupling		direct	elastic coupling	elastic coupling	elastic coupling	reduction gear	reduction gear	reduction gear	reduction gear

STANDARD EQUIPMENT

CODE: IPPR40020
HANDGRIP G6000 M22



CODE: LCPR40013
EXTENSION INOX P70 + HY.JET



CODE: UGLN49990
H.P. NOZZLE 1/4 UG.25034 (FOR 1811/2013/2515)



CODE: UGLN05199
H.P. NOZZLE 1/4 UG.2505 (FOR 2216/2217)



CODE: UGLN49995
H.P. NOZZLE 1/4 UG.25065 (FOR 2021)



CODE: TBAP25324
HIGH PRESSURE HOSE 10 m



OPTIONAL ACCESSORIES

CODE: RCIN10810
HOSE COUPLINGS M22



CODE: LCPR24906
LANCE WITH DOUBLE NOZZLE HOLDER



CODE: LCPR29360
MUDGUARD LANCE P90



CODE: TBAP23853
DRAIN KIT 10 m



CODE: TBAP24406
DRAIN KIT 20 m



CODE: TBAP40062
FLEXIBLE HOSE 15 m



CODE: TBAP44379
FLEXIBLE HOSE 20 m



CODE: LCPR40009
TURBO LANCE P70 Ø 035 (FOR 1811/2013/2515)



CODE: LCPR41973
TURBO LANCE P70 Ø 055 (FOR 2216/2217)



CODE: LCPR88522
TURBO LANCE P70 Ø 065 (FOR 2021)



CODE: KTRI40186
HOSE REEL KIT



CODE: LCPR40040
FOAMER HEAD KIT 1 l



CODE: LCPR14858
SANDBLASTER KIT Ø 1,4 mm (FOR 1811/2013/2515)



CODE: LCPR13557
SANDBLASTER KIT Ø 1,6 mm (FOR 2216/2217)



CODE: LCPR14860
SANDBLASTER KIT Ø 1,7 mm (FOR 2021)



CODE: PRCH00065
SAND BAG 50 Kg



CODE: LCLC49492
LANCE FOR WASHING FLOORS 0,35 (FOR 1811/2013)



CODE: LCLC49494
LANCE FOR WASHING FLOORS 0,55 (FOR 2021)



CODE: KTRI00038
INJECTOR KIT

