



SCRUBBER DRIERS - WALK BEHIND

# CT55

MAX PRODUCTIVITY

2700 m<sup>2</sup>/h

BATTERIES  
RUNNING TIME

2,5 h

WATER TANK  
RUNNING TIME

60'  
working session



DOUBLE BRUSH VERSION



ROLLER VERSION



MOST FREQUENTLY USE



INNOVATIONS



SPECS



INTUITIVE CONTROL PANEL



SEPARATE DETERGENT DOSING SYSTEM. (OPTIONAL)



ANTI-FOAM SYSTEM WITH SPECIAL ELECTROMECHANICAL SUCTION MOTOR PROTECTION

## TECHNICAL DATA

		CT55 B55	CT55 BT55	CT55 C55	CT55 BT60	CT55 BT55 R
Code		LPTB01516	LPTB01517	LPTB01102	LPTB01518	LPTB01519
<b>PERFORMANCE</b>						
Max theoretical productivity	m <sup>2</sup> /h	1925	2475	2475	2700	2475
Cleaning path	mm	550	550	550	600	550
Water tank capacity (solution recovery)	l	55/60	55/60	55/60	55/60	55/60
Max running time	min	140	140	Unlimited	140	140
Voltage	V-Ah	24(2x12)-105 GEL	24(2x12)-105 GEL	230-50	24(2x12)-105 GEL	24(2x12)-105 GEL
Installed power	W	480	480	550	480	480
Brush pressure	kg	27	23	30	30	13,6/18,6
Squeegee width	mm	815	815	815	815	815
Max speed	km/h	5	5	5	5	5
Weight	kg	154	169,5	169,5	175,5	175,5
Dimension (LxWxH)	mm	1190x685x1018	1190x685x1018	1190x640x1018	1190x685x1018	1190x685x1018

## STANDARD EQUIPMENT

### BRUSHES

	CT55 B55	CT55 BT55	CT55 C55	CT55 BT60	CT55 BT55 R
PPL soft	SPPV01505	SPPV01505	SPPV01505	SPPV01473	-
Cylindrical brush - PPL soft Ø 0,3 mm	-	-	-	-	SPPV01163

### SQUEEGEE BLADES

LATEX FRONT BLADE	MPVR08039 - 880mm	MPVR08039 - 880mm	MPVR08039 - 880mm	MPVR08039 - 880mm	MPVR08039 - 880mm
LATEX REAR BLADE	MPVR08035 - 900mm	MPVR08035 - 900mm	MPVR08035 - 900mm	MPVR08035 - 900mm	MPVR08035 - 900mm

## CONSUMABLES (Codes available on price list)

### BRUSHES



### CYLINDRICAL BRUSHES



### PADS/SUPER PADS



### SQUEEGEE BLADES



## OPTIONAL ACCESSORIES

CODE: KTRI02141  
CHEM DOSE KIT



CODE: MPVR05611  
SPLASH GUARD



CODE: KTRI01573  
DISCHARGE HOSE



CODE: KTRI01870  
SOLUTION TANK DRAIN  
AND LEVEL HOSE KIT



CODE: KTRI02080  
DEBRIS COLLECTOR



CODE: KTRI02257  
EXTERNAL SUCTION KIT



## BATTERIES AND BATTERY CHARGERS

BATTERIES	N°	CHARACTERISTICS	DIMENSION	RUNNING TIME	BATTERY CHARGERS
IPC gel battery BAAC00105	2	12V 105 Ah [ C5 ]	345x170x285	150 min	On board battery charger 24V 10 Ah- KTRI01703 Stand alone high frequency BLS010 - BACA00133
EXIDE gel battery BAAC00024	2	12V 105 Ah [ C5 ]	345x174x283	150 min	On board battery charger 24V 10 Ah- KTRI01703 Stand alone high frequency BLS010 - BACA00133
Acid tubular plate BAAC00136	2	12V 85 Ah [ C5 ]	308x175x225	160 min	On board battery charger 24V 10 Ah- KTRI01703 Stand alone high frequency BLS010 - BACA00133 Stand alone low frequency 24V 12 Ah BACA00060
Dry charge flate plate BAAC00009	2	12V 105 Ah [ C5 ]	261x171x210	160 min	On board battery charger 24V 10 Ah- KTRI01703 Stand alone high frequency BLS010 - BACA00133 Stand alone low frequency 24V 12 Ah BACA00060
Acid tubular plate BAAC00070	2	12V 118 Ah [ C5 ]	345x170x285	160 min	On board battery charger 24V 10 Ah- KTRI01703 Stand alone high frequency BLS010 - BACA00133 Stand alone low frequency 24V 12 Ah BACA00060

IP Cleaning S.p.A.

Treviso 63 - 30026 Summaga di Portogruaro (VE) - Italy  
+39 0421 205511 - Fax +39 0421 204227 - infodipcworldwide.com - www.ipcworldwide.com

