

GTE GREEN TUBE

PRESSURE

Up to 5.0 bar 4.0 l/min

FLOW RATE

EXCLUSIVE CHARACTERISTICS

- **POWER FILTER**
- **ERGONOMICS**
- **DURABILITY**
- **POWER PUMP**

TECHNICAL	DATA	

Code PERFORMANCE		APTA40009
Operating pressure	bar	up to 5
Pure water flow	l/min	2-4
Water in/out connections	gas	3/4'
Max poles lenght	m	16
Productivity	m²/h	up to 100
Power supply	Ph-V-Hz	1-230-50
Absorbed power	kW	0.3

MOST FREQUENTLY USE

CONSTRUCTION INDUSTRY

GREEN ENERGIES

NAUTICAL/AUTO/TRANSPORTS

GREENHOUSES/GLASSHOUSES/ TENSILE STRUCTURES

STANDARD EQUIPMENT

CODE: FTAC40002 **REVERSE OSMOSIS MEMBRANE**

Dimension (LxWxH)

Weight



CODE: PRCH400034 **POWDER FOR OSMOTIC MEMBRANE FILTER MAINTENANCE**



FILTER KIT: 1PCS SEDIMENTATION,

1PCS ACTIVE CARBON, 1PCS

cm

kg

CODE: KTRI40147



CODE: TBBP40079 **DRAINAGE TUBE**



CODE: TBFX40008

WITH FITTINGS

15M FLEXIBLE HOSE

GTE

33x41x145

28

CODE: CNPR40007 **GASKET LUBRICANT**



CODE: AZMC40006

HAND-HELD TDS







