



PURE WATER CLEANING SYSTEM

# HPB HIGH PURE



**PRESSURE**

7,0 bar

**FLOW RATE**

5,0 l/min

**EXCLUSIVE CHARACTERISTICS**

- ▶ POWER FILTER
- ▶ ERGONOMICS
- ▶ DURABILITY
- ▶ POWER PUMP

**TECHNICAL DATA**

		<b>HPB</b>
Code		APTA40016
<b>PERFORMANCE</b>		
Operating pressure	bar	5-7
Pure water flow	l/min	2-5
Water in/out connections	gas	3/4"
Max poles lenght	m	16 (also with 2 poles)
Productivity	m <sup>2</sup> /h	up to 200
Power supply		12V / 140W
Absorbed power	kW	53x50x127
Dimension (LxWxH)	cm	50
Weight	kg	28

**MOST FREQUENTLY USE**

CONSTRUCTION INDUSTRY

GREEN ENERGIES

NAUTICAL/AUTO/TRANSPORTS

GREENHOUSES/GLASSHOUSES/  
TENSILE STRUCTURES

**STANDARD EQUIPMENT**

CODE: FTAC40002  
**REVERSE OSMOSIS  
MEMBRANE**



CODE: PRCH400034  
**POWDER FOR  
OSMOTIC MEMBRANE  
FILTER MAINTENANCE**



CODE: KTRI40106  
**FILTER KIT: 1PCS SEDIMENTATION,  
1PCS ACTIVE CARBON, 1PCS  
DEIONIZING RESIN CARTRIDGE**



CODE: TBBP40010  
**DRAINAGE TUBE**



CODE: TBFX40009  
**15M FLEXIBLE HOSE  
WITH FITTINGS**



CODE: VVSF40011  
**FLOW ONTROL VALVE**



CODE: AZMC40006  
**HAND-HELD TDS  
METER**



CODE: CNPR40007  
**GASKET LUBRICANT**



IP Cleaning S.p.A.

Viale Treviso 63 - 30026 Summaga di Portogruaro (VE) - Italy  
Tel. +39 0421 205511 - Fax +39 0421 204227 - info@ipcworldwide.com - www.ipcworldwide.com

Information about waterlift and airflow refers to single motors. Specifications, descriptions and pictures are supplied as indicative: rights to technical modifications reserved without prior notice.