



PURE WATER CLEANING SYSTEM

HPB HIGH PURE



PRESSURE

7 bar

FLOW RATE

5 l/min

EXCLUSIVE CHARACTERISTICS

- ▶ POWER FILTER
- ▶ ERGONOMICS
- ▶ DURABILITY
- ▶ POWER PUMP

TECHNICAL DATA

	HPB	
Code	APTA40016	
PERFORMANCE		
Operating pressure	bar	5-7
Pure water flow	l/min	2-5
Water in/out connections	gas	3/4"
Max poles lenght	m	16 (also with 2 poles)
Productivity	m ² /h	up to 200
Power supply		12V / 140W
Absorbed power	kW	53x50x127
Dimension (LxWxH)	cm	50
Weight	kg	28

MOST FREQUENTLY USE

CONSTRUCTION INDUSTRY



GREEN ENERGIES



NAUTICAL/AUTO/TRANSPORTS



**GREENHOUSES/GLASSHOUSES/
TENSILE STRUCTURES**



STANDARD EQUIPMENT

CODE: FTAC40002
**REVERSE OSMOSIS
MEMBRANE**



CODE: PRCH400034
**POWDER FOR
OSMOTIC MEMBRANE
FILTER MAINTENANCE**



CODE: KTRI40106
**FILTER KIT: 1PCS SEDIMENTATION,
1PCS ACTIVE CARBON, 1PCS
DEIONIZING RESIN CARTRIDGE**



CODE: TBBP40010
DRAINAGE TUBE



CODE: TBFX40009
**30 m FLEXIBLE HOSE
WITH FITTINGS**



CODE: VVSF40018
FLOW ONTROL VALVE



CODE: AZMC40006
**HAND-HELD TDS
METER**



CODE: CNPR40007
GASKET LUBRICANT

