



PURE WATER CLEANING SYSTEM

HPG HIGH PURE

PRESSURE

8 bar

FLOW RATE

7 l/min



PETROL ENGINE

EXCLUSIVE CHARACTERISTICS

- ▶ POWER FILTER
- ▶ ERGONOMICS
- ▶ DURABILITY
- ▶ POWER PUMP
- ▶ MANOMETER

TECHNICAL DATA

		HPG
Code		APTA40012
PERFORMANCE		
Operating pressure	bar	7-8
Pure water flow	l/min	3-7
Water in/out connections	gas	3/4"
Max poles lenght	m	16 (also with 2 poles)
Productivity	m ² /h	up to 200
Engine type		Honda GX120 (gasoline)
Engine power	Hp	4
Dimension (LxWxH)	cm	53x67x127
Weight	kg	60

MOST FREQUENTLY USE

CONSTRUCTION INDUSTRY

GREEN ENERGIES

NAUTICAL/AUTO/TRANSPORTS

GREENHOUSES/GLASSHOUSES/
TENSILE STRUCTURES

STANDARD EQUIPMENT

CODE: FTAC40002
REVERSE OSMOSIS
MEMBRANE



CODE: PRCH400034
POWDER FOR
OSMOTIC MEMBRANE
FILTER MAINTENANCE



CODE: KTRI40106
FILTER KIT: 1PCS SEDIMENTATION,
1PCS ACTIVE CARBON, 1PCS
DEIONIZING RESIN CARTRIDGE



CODE: VVSF40018
FLOW ONTROL VALVE



CODE: TBFX40009
30 m FLEXIBLE HOSE
WITH FITTINGS



CODE: CNPR40007
GASKET LUBRICANT



CODE: AZMC40006
HAND-HELD TDS
METER



CODE: TBBP40010
DRAINAGE TUBE

