



HIGH-PRESSURE WASHERS - COLD WATER STATIONARY

ML CMP

PRESSURE

130-210
bar

FLOW RATE

600-1000
l/h

ABSORBED POWER

3-7,5 kW

EXCLUSIVE CHARACTERISTICS

- ▶ BY-PASS - BYP
- ▶ THERMOSTATIC VALVE - TSV
- ▶ DELAYED TOTAL STOP - DTS
- ▶ MICRO LEAKAGE CONTROL - MLC
- ▶ FLOODING PREVENTION SYSTEM - FPS
- ▶ NOOZLE CLOG CONTROL - NCC
- ▶ WORKING HOURS COUNTER - WHC
- ▶ DRY RUNNING PROTECTION - DRP
- ▶ INTELLIGENT PROPORTIONAL SWITCHING OFF - IPSF



MOST FREQUENTLY USE

AUTOMOTIVE



AGRICULTURE



CONSTRUCTION INDUSTRY



MUNICIPALITIES



DIY AND GARDENING



HEAVY INDUSTRY



INNOVATIONS



MSC™
MULTIFUNCTION
SAFETY
CONTROL

SPECS



EASY ACCESS TO ALL
COMPONENTS FOR AN EASY
MAINTENANCE



HIGH CAPACITY INLET WATER
FILTER



BY-PASS VALVE IS PROVIDED
WITH 1 HOLDING METAL
PLATE IN ORDER TO PROTECT
IT FROM MECHANICAL STRESS

TECHNICAL DATA

		BY-PASS				DELAYED TOTAL STOP			
		ML CMP 1310P M	ML CMP 1813P T	ML CMP 1915P T	ML CMP 2117P T	ML CMP D1310P M	ML CMP D1813P T	ML CMP D1915P T	ML CMP D2117P T
Code		IDAF40360	IDAF40361	IDAF40362	IDAF40363	IDAF40486	IDAF40535	IDAF40536	IDAF40537
PERFORMANCE									
Operating pressure	bar/Mpa	30-130/3-13	30-180/3-18	30-190/3-19	30-210/3-21	30-130/3-13	30-180/3-18	30-190/3-19	30-210/3-21
Flow rate	l/h	600	800	900	1000	600	800	900	1000
Inlet water max. temperature	°C	50	50	50	50	50	50	50	50
Power supply	Ph-V-Hz/A	1-230-50/15	3-400-50/8,5	3-400-50/9,5	3-400-50/12	1-230-50/15	3-400-50/8,5	3-400-50/9,5	3-400-50/12
Absorbed power	kW	3	5,1	5,1	7,5	3	5,1	5,1	7,5
Motor pole/rpm		4-1400	2-2800	4-1400	4-1400	4-1400	2-2800	4-1400	4-1400
Remote control		BYP	BYP	BYP	BYP	DTS	DTS	DTS	DTS
Pump/head/pistons		lpc plunger/ brass/ceramic	lpc plunger/ brass/ceramic	lpc plunger/ brass/ceramic	lpc plunger/ brass/ceramic	lpc plunger/ brass/ceramic	lpc plunger/ brass/ceramic	lpc plunger/ brass/ceramic	lpc plunger/ brass/ceramic
Dimension (LxWxH)	cm	68x48x32	68x48x32	68x48x32	68x48x32	68x48x32	68x48x32	68x48x32	68x48x32
Weight	kg	46	50	55	67	46	50	55	67

STANDARD EQUIPMENT

CODE: IPIP40014
GRIP G6000 BAYONET



CODE: LCLC40004
P70 INOX EXTENSION
BAYONET



CODE: UGLN49990
HIGH-PRESSURE NOZZLE
(FOR 1310)



CODE: UGLN49991
HIGH-PRESSURE NOZZLE
(FOR 1813)



CODE: UGLN49987
HIGH-PRESSURE NOZZLE
(FOR 1915/2117)



CODE: TBAP25324
HIGH-PRESSURE HOSE
MT 10



OPTIONAL ACCESSORIES

CODE: KTRI37674
HOSE REEL KIT



CODE: AVTB39119
INOX HOSE REEL KIT



CODE: RCIN10810
HOSE COUPLINGS



CODE: KTRI28914
ROTATING ARM



CODE: LCPR40039
FOAMER HEAD



CODE: LCPR14858
SANDBLASTER KIT D.1,4
(FOR 1310)



CODE: LCPR13557
SANDBLASTER KIT D.1,6
(FOR 1915/2117)



CODE: PRCH00065
SAND BAG 50KG



CODE: KTRI40311
MAINTENANCE KIT 500H
(FOR 1310)



CODE: KTRI40317
MAINTENANCE KIT 500H
(FOR 1813)



CODE: KTRI40313
MAINTENANCE KIT 500H
(FOR 1915)



CODE: KTRI40338
MAINTENANCE KIT 500H
(FOR 2117)



IP Cleaning S.p.A.

Viale Treviso 63 - 30026 Summaga di Portogruaro (VE) - Italy
Tel. +39 0421 205511 - Fax +39 0421 204227 - info@ipcworldwide.com - www.ipcworldwide.com



Information about waterlift and airflow refers to single motors.
Specifications, descriptions and pictures are supplied as indicative: rights to technical modifications reserved without prior notice.