



PLANET 200 CJET PLANET 200 UJET

EXCLUSIVE FEATURES

- ▶ INDEPENDENT MOTORS WITH LIGHT SWITCHES
- ▶ RELIABLE CONSTRUCTION FOR INTENSIVE USE
- ▶ DETACHABLE TANK AND SOLID CART
- ▶ TANGENTIAL OR METAL INLET
- ▶ DOUBLE STAGE MOTORS AND TURBINE
- ▶ BIG AND BRAKED WHEELS
- ▶ VISUAL FILLING INDICATOR
- ▶ INDUSTRIAL FRAMEWORK WITH AISI 304 WITH DETACHABLE TANK
- ▶ TANGENTIAL INLET AND CONVEYOR CONE
- ▶ VACUUM RELIEF VALVE AND FILTRATION LEVEL INDICATOR
- ▶ DOUBLE CARTRIDGE FILTRATION CLASS M/H
- ▶ AIR SUPPLY CONTROL AND ELECTROVALVES
- ▶ AUTOMATIC FILTER CLEANING SYSTEM
- ▶ FILTER LOCK SEPARATOR AND AIR CONTAINER

	PLANET 200 CJET	PLANET 200 UJET
Code	ASID00386	ASID00402
TECHNICAL DATA		
Usage	DRY	DRY
Number of phases	single phase	single phase
Voltage	220-240	220-240
Frequency	50-60	50-60
N. and type of motor	3x2 stages	3x2 stages
Power	3600-3800 max	3600-3800 max
Water lift	2795	2795
Airflow	630	630
Tank Capacity	60	60
Diameter of inlet	70	70
Filtering surface	24000	24000
Sound Pressure Level	76	76
Dimensions (LxWxH)	660x900x1630	660x900x1630
Weight	65	65

STANDARD EQUIPMENT

CODE: FTDP00489
POLYESTER CARTRIDGE N.
2 PCS (2X12.000 cm²)



OPTIONAL ACCESSORIES

Basic tool kit Ø50-70 mm	PMDT00444
Anti-Static tool kit Ø50-70 mm	PMDT00426
Anti-oil tool kit Ø50-70 mm	PMDT00448
Polyester/hepa cartridge	FTDP00491
Hepa cartridge	FTDP40006