



HIGH-PRESSURE WASHERS - COLD WATER

PW-C25 PLUS

PRESSURE

130÷180
bar

FLOW RATE

540÷800
l/h

ABSORBED POWER

2,7÷4,7
kW



EXCLUSIVE CHARACTERISTICS

- ▶ IMMEDIATE TOTAL STOP - ITS ("I" MODELS)
- ▶ BY-PASS - BYP
- ▶ THERMOSTATIC VALVE - TSV (BY PASS MODELS)

MOST FREQUENTLY USE

AUTOMOTIVE

AGRICULTURE

CONSTRUCTION INDUSTRY

MUNICIPALITIES

DIY AND GARDENING

HEAVY INDUSTRY

INNOVATIONS



G6000™
CERAMIC
TECH GUN

SPECS



SOLID STRUCTURE:
RESISTANT TO SHOCKS,
ATMOSPHERIC AGENTS AND
CHEMICAL CORROSION



IPC PUMP WITH SEPARATE
BY-PASS, AND ADJUSTABLE
PRESSURE



PROFESSIONAL HOSE REEL

TECHNICAL DATA

| | | BY-PASS MODELS | | | IMMEDIATE TOTAL STOP MODELS | | |
|-----------------------------|-----------|-------------------------------|-------------------------------|-------------------------------|-------------------------------|-------------------------------|-------------------------------|
| | | PW-C25P 1310P4 M | PW-C25P 1509P M | PW-C25P 1813P T | PW-C25P I1310P4 M | PW-C25P I1509P M | PW-C25P I813P T |
| Code | | IDAF94186 | IDAF94178 | IDAF94182 | IDAF94187 | IDAF94170 | IDAF94174 |
| PERFORMANCE | | | | | | | |
| Operating pressure | bar/Mpa | 30-130/3-13 | 30-150/3-15 | 30-180/3-18 | 30-130/3-13 | 30-150/3-15 | 30-180/3-18 |
| Flow rate | l/h | 600 | 540 | 800 | 600 | 540 | 800 |
| Max inlet water temperature | °C | 50 | 50 | 50 | 50 | 50 | 50 |
| Power supply | Ph-V-Hz/A | 1-230-50/13,3 | 1-230-50/12 | 3-400-50/8,6 | 1-230-50/13,3 | 1-230-50/12 | 3-400-50/8,6 |
| Absorbed power | kW | 2,7 | 2,8 | 4,7 | 2,7 | 2,8 | 4,7 |
| Motor pole/rpm | | 4-1400 | 2-2800 | 2-2800 | 4-1400 | 2-2800 | 2-2800 |
| Remote control | | BYP | BYP | BYP | ITS | ITS | ITS |
| Pump/head/pistons | | lpc plunger/brass/ ceramic | lpc plunger/brass/ ceramic | lpc plunger/brass/ ceramic | lpc plunger/brass/ ceramic | lpc plunger/brass/ ceramic | lpc plunger/brass/ ceramic |
| Detergent tank | l | 3 | 3 | 3 | 3 | 3 | 3 |
| Detergent delivery | | low pressure | low pressure | low pressure | low pressure | low pressure | low pressure |
| Dimension (LxWxH) | cm | 49x40x93 | 49x40x93 | 49x40x93 | 49x40x93 | 49x40x93 | 49x40x93 |
| Weight | Kg | 35 | 37 | 40 | 35 | 37 | 40 |

STANDARD EQUIPMENT

CODE: IPPR40020
HANDGRIP G6000



CODE: LCPR40049
EXTENSION P580
Ø 1,40BEI (FOR 1310)



CODE: LCPR40057
EXTENSION P580
Ø 1,20GL (FOR 1509)



CODE: LCPR40046
EXTENSION P580
Ø 1,50AZZ (FOR 1813)



CODE: LCPR40016
TURBO LANCE TTR-16 M22
1,40 (FOR 1310)



CODE: LCPR93178
TURBO LANCE TTR-16 M22
1,35 (FOR 1509)



CODE: LCPR93177
TURBO LANCE TTR-16 M22
1,30 (FOR 1813)



CODE: TBAP93827
HIGH PRESSURE HOSE
12 m



OPTIONAL ACCESSORIES

CODE: LCPR29360
MUDGUARD LANCE P90



CODE: TBAP23853
DRAIN KIT 10 m



CODE: LCLC49492
LANCE FOR WASHING
FLOORS (FOR 1509)



CODE: LCLC49493
LANCE FOR WASHING
FLOORS (FOR 1310/1813)



CODE: LCPR40040
FOAMER KIT



CODE: LCPR14858
SANDBLASTER KIT
Ø 1,4 mm (FOR 1310/1813)



CODE: LCPR24943
SANDBLASTER KIT
Ø 1,3 mm (FOR 1509)



CODE: PRCH00065
SAND BAG 50 Kg



CODE: SPID24939
FIXED HYDROBRUSH
LANCE



CODE: KTRI40312
MAINTENANCE KIT 500H
(FOR 1310P4)



CODE: KTRI40318
MAINTENANCE KIT 500H
(FOR 1509/1813)

