



STEAM GENERATORS

SG-40

PRESSURE

5,0 bar

FLOW RATE

100 g/min

ABSORBED POWER

2,9 kW

EXCLUSIVE CHARACTERISTICS

- ▶ POWER BOILER
- ▶ ANTI-BUG
- ▶ POWER FILTER
- ▶ SAFETY
- ▶ ERGONOMICS
- ▶ FLEX POWER
- ▶ DURABILITY



MOST FREQUENTLY USE

AUTOMOTIVE



HO.RE.CA.



FOOD INDUSTRY AND RETAILERS



LARGE COMMON AREAS



SPECS



HANDLE FOR AN EASY TRANSPORTATION



ELECTROMECHANICAL CONTROL PANEL WITH PROTECTION AGAINST HUMIDITY



NON-MARKING WHEELS

TECHNICAL DATA

		SG-40 5008 M
Code		GNVA40018
PERFORMANCE		
Operating pressure	bar/Mpa	2,5-5/0,25-0,5
Steam flow rate	g/min	0-100
Max steam temperature	°C	150
Start up time	min	~ 6
Power supply	Ph-V-Hz	1-230-50
Max absorbed power	kW	2,9
Boiler volume	l	3
Water tank	l	6
Dimension (LxWxH)	cm	66x43x67
Weight	kg	19,5

STANDARD EQUIPMENT

CODE: IPIP45815
**HANDGRIP + HOSE
STEAM 5MT**



CODE: KTRI40275
**STEAM ONLY
ACCESSORIES KIT**



CODE: MPVR88900
TANK 5L



OPTIONAL ACCESSORIES

CODE: IPIP40003
**HANDGRIP + HOSE
STEAM 8MT**



CODE: KTRI89495
TROLLEY



CODE: KTRI40269
**DESCALING KIT
(10 PHIALS)**

