



STEAM GENERATORS

# SG-45 (SOFT TOUCH PANEL)

PRESSURE

5,0 bar

FLOW RATE

100 g/min

ABSORBED POWER

2,9 kW



## EXCLUSIVE CHARACTERISTICS

- ▶ POWER BOILER
- ▶ ANTI-BUG
- ▶ POWER FILTER
- ▶ AUTOMATIC SHUTDOWN
- ▶ SAFETY
- ▶ ERGONOMICS
- ▶ FLEX POWER
- ▶ DURABILITY

## MOST FREQUENTLY USE

AUTOMOTIVE



HO.RE.CA.



FOOD INDUSTRY AND RETAILERS



LARGE COMMON AREAS




## SPECS



STEAM HOSE HOOK  
EQUIPPED WITH SAFETY  
PANEL



ROTARY KNOB FOR STEAM  
FLOW RATE CONTROLLER



NON-MARKING WHEELS

## TECHNICAL DATA

		<b>SG-45 5008 M</b>
Code		GNVA40020
PERFORMANCE		
Operating pressure	bar/Mpa	2,5-5/0,25-0,5
Steam flow rate	g/min	0-100
Max steam temperature	°C	150
Start up time	min	~ 6
Power supply	Ph-V-Hz	1-230-50
Max absorbed power	kW	2,9
Boiler volume	l	3
Water tank	l	6
Dimension (LxWxH)	cm	66x43x67
Weight	kg	20

## STANDARD EQUIPMENT

CODE: IPIP45815  
HANDGRIP + HOSE  
STEAM 5MT



CODE: KTRI40275  
STEAM ONLY  
ACCESSORIES KIT



CODE: MPVR88900  
TANK 5L



## OPTIONAL ACCESSORIES

CODE: IPIP40003  
HANDGRIP + HOSE  
STEAM 8MT



CODE: KTRI89495  
TROLLEY



CODE: KTRI40269  
DESCALING KIT  
(10 PHIALS)

