



HIGH-PRESSURE WASHERS - HOT WATER

# TWOCK-H

PRESSURE

130÷200  
bar

FLOW RATE

1800÷2500  
l/h

ABSORBED POWER

11÷12,8  
kW

## EXCLUSIVE CHARACTERISTICS

- ▶ DELAYED TOTAL STOP - DTS
- ▶ DRY RUNNING PROTECTION - DRP
- ▶ LIMESCALE/CORROSION PROTECTION UNIT - LCPU
- ▶ ANTI-SCALE LEVEL CONTROL - ALC
- ▶ FUEL LEVEL CONTROL - FLC
- ▶ INFRARED FLAME CONTROL SYSTEM - FCS



## MOST FREQUENTLY USE

AUTOMOTIVE



AGRICULTURE



CONSTRUCTION INDUSTRY



MUNICIPALITIES



HEAVY INDUSTRY



## INNOVATIONS



G6000™  
CERAMIC  
TECH GUN



M421  
ANTI-SCALE

## SPECS



FLEXIBLE COUPLING BETWEEN MOTOR AND PUMP



CONTROL PANEL PROVIDED WITH EMERGENCY SHUTDOWN



PLUNGER PUMP WITH SIX CERAMIC PISTONS AND TWO BRASS HEADS

## TECHNICAL DATA

		<b>TWOCK-H D1341PIT</b>	<b>TWOCK-H D2030PIT</b>
Code		IDAC49714	IDAC49713
<b>PERFORMANCE</b>			
Operating pressure	bar/Mpa	30-130/3-13	30-200/3-20
Flow rate	l/h	2500	1800
Outlet water temperature	°C	30-150	30-150
Power supply	Ph-V-Hz/A	3-400-50/24,9	3-400-50/24
Absorbed power	kW	11	12,8
Motor pole/rpm		4-1400	6-1000
Remote control		DTS	DTS
Pump/head/pistons		lpc plunger/ 2 brass/ceramic	lpc plunger/ 2 brass/ceramic
Boiler thermal power	kW	81	81
Fuel consumption	kg/h	8,4 x 2	8,4 x 2
Fuel tank	l	54	54
Detergent tank	l	-	-
Detergent delivery		high pressure	high pressure
Dimension (LxWxH)	cm	140x86x86	140x86x86
Weight	kg	448	480

## STANDARD EQUIPMENT

CODE: IPPR40020  
HANDGRIP G6000



CODE: LCPR40159  
EXTENSION P70 INOX 0°



CODE: UGLN02317  
HIGH PRESSURE NOZZLE  
(FOR 1341)



CODE: UGLN02312  
HIGH PRESSURE NOZZLE  
(FOR 2030)



CODE: TBAP40011  
HIGH PRESSURE HOSE  
15 m



## OPTIONAL ACCESSORIES

CODE: LCPR29363  
STEAM LANCE - P70



CODE: PRCH40039  
ANTI-SCALE TREATMENT  
M421 1 Kg X6



CODE: PRCH40040  
ANTI-SCALE TREATMENT  
M421 10 Kg



CODE: LCPR40089  
EXTENSION P70 TURBO  
D.1.0 (FOR 2030)



CODE: KTRI28935  
LANCE HOLDER



CODE: KTRI28914  
ROTATING ARM



CODE: KTRI29366  
PLUNGER EJECTOR DEVICE



CODE: AVTB39119  
INOX HOSE REEL KIT

