



VACUUM CLEANERS - SPECIAL SOLUTIONS - FLOODED AREA EMPTYING

GS 2/62 SUB

POWER MAX

2400
W

WATER LIFT

2470
mmH₂O

AIRFLOW

420
m³/h

TANK CAPACITY

62
l



PUMP
OUT

EXCLUSIVE FEATURES

- ▶ AP TUBE
- ▶ INNOVATIVE GASKET
- ▶ STRONG HOOKS
- ▶ INDEPENDENT MOTORS WITH LIGHT SWITCHES
- ▶ SEALANT FLOATER & INTEGRATED ANTIFOAM SYSTEM
- ▶ RELIABLE CONSTRUCTION FOR INTENSIVE USE
- ▶ SUBMERSIBLE PUMP
- ▶ DOUBLE STAGE MOTORS

MOST FREQUENTLY USE



INNOVATIONS



SPECS



PROFESSIONAL SUBMERSIBLE PUMP



INTEGRATED ANTI-FOAM SYSTEM



ELECTRIC POWER SOCKET ON BOARD (FOR PUMP)

TECHNICAL DATA

| | | GS 2/62 SUB |
|--|--------------------|--------------------|
| Code | | ASD015119 |
| PERFORMANCE | | |
| Usage | | WET |
| Motor | | 2x2 stage |
| Power | W | 2400 max |
| Voltage | V | 220-240 |
| Water lift | mmH ₂ O | 2470 |
| Airflow | m ³ /h | 420 |
| Tank Capacity/Material | l | 62/steel |
| Cable length | m | 8,5 |
| Sound Pressure Level (EN 60704-1; EN 60704-2-1; IEC 60335-2-69) | dB(A) | 77 |
| Pump type | | Plastic |
| Pump power | W | 370 |
| Pump capacity | l/min | 180 |
| Delivery head | m | 7 |
| Diameter of accessories | mm | 38 |
| Dimensions (LxWxH) | mm | 550x600x960 |
| Weight | kg | 21,0 |

STANDARD EQUIPMENT

PMDT00350 ACCESSORIES KIT FOR SUB Ø38 MM COMPOSED OF:

CODE: TBFX28237
FLEXIBLE HOSE 2,5 m
Ø38 mm



CODE: LAFN43048 (FOR 1 PC)
ALUMINIUM/PLASTIC
TUBE 50 cm Ø38 mm
(MACHINE COMES WITH 2PCS)



CODE: MPVR43047
HANDLE WITH AIR
REGULATOR Ø38 mm



CODE: SPPV43051
WET TOOL Ø38 mm



OPTIONAL ACCESSORIES

CODE: TBBP00719
ANTIFREEZE HOSE 5 m
Ø30 mm



CODE: FSVR00129
HOSE CLAMP 30X45



To connect to water flow valve