



VACUUM CLEANERS - SPECIAL SOLUTIONS - STOVES & OVEN CLEANING

AS 1/18 ASH

POWER MAX	WATER LIFT	AIRFLOW	TANK CAPACITY
1300 w	2870 mmH ₂ O	210 m ³ /h	18 l

EXCLUSIVE FEATURES

- ▶ AP TUBE
- ▶ INNOVATIVE GASKET
- ▶ STRONG HOOKS
- ▶ MULTI STAGE FILTRATION
- ▶ SUITABLE FOR VACUUMING COLD ASHES FROM STOVES, FIREPLACES AND BARBECUES



ONLY FOR COLD ASH

MOST FREQUENTLY USE



INNOVATIONS



SPECS



WASHABLE CARTRIDGE



PREFILTER FOR CARTRIDGE



AP TUBE

TECHNICAL DATA

		AS 1/18 ASH
Code		ASD003641
PERFORMANCE		
Usage		DRY
Motor		1
Power	W	1100-1300 max
Voltage	V	220-240
Water lift	mmH ₂ O	2870
Airflow	m ³ /h	210
Tank Capacity/Material	l	18/steel
Cable length	m	8,5
Filtering surface	cm ²	2260
Sound Pressure Level (EN 60704-1; EN 60704-2-1; IEC 60335-2-69)	dB(A)	64
Diameter of accessories	mm	36
Dimensions (LxWxH)	mm	380x380x450
Weight	kg	11

STANDARD EQUIPMENT

CODE: FTDP40015
WASHABLE CARTRIDGE



CODE: FTDP40018
WASHABLE PREFILTER



CODE: -
PAPER BAG



CODE: TBFX72031
FLEXIBLE HOSE 2 m
Ø36 mm



CODE: LAFN28238
ALUMINIUM/PLASTIC
TUBE Ø36 mm



CODE: SPPV28242
FLAT LANCE Ø36 mm



OPTIONAL ACCESSORIES

CODE: KTRI02639
PAPER BAG SET OF 10 PCS



X10