



VACUUM CLEANERS - SPECIAL SOLUTIONS - FLOODED AREA EMPTYING

GC 2/107 SUB+

POWER MAX

2400 W

WATER LIFT

2470 mmH₂O

AIRFLOW

420 m³/h

TANK CAPACITY

107 l

EXCLUSIVE FEATURES

- ▶ AP TUBE
- ▶ INNOVATIVE GASKET
- ▶ STRONG HOOKS
- ▶ INDEPENDENT MOTORS WITH LIGHT SWITCHES
- ▶ SEALANT FLOATER & INTEGRATED ANTIFOAM SYSTEM
- ▶ TIPPING TROLLEY
- ▶ RELIABLE CONSTRUCTION FOR INTENSIVE USE
- ▶ SUBMERSIBLE PUMP
- ▶ DOUBLE STAGE MOTORS



PUMP OUT

MOST FREQUENTLY USE

AGRICULTURE



CONSTRUCTION



HARDWARE CUSTOMER



HEAVY INDUSTRY



AUTOMOTIVE



INNOVATIONS



SPECS



HIGH EFFICIENCY STAINLESS STEEL SUBMERSIBLE PUMP FOR INDUSTRIAL APPLICATION



WATER FLOW VALVE



TIPPING TROLLEY

TECHNICAL DATA

		GC 2/107 SUB+
Code		ASD015530
PERFORMANCE		
Usage		WET
Motor		2x2 stage
Power	W	2400 max
Voltage	V	220-240
Water lift	mmH ₂ O	2470
Airflow	m ³ /h	420
Tank Capacity/Material	l	107/plastic (polyethylene)
Cable length	m	8,5
Sound Pressure Level (EN 60704-1; EN 60704-2-1; IEC 60335-2-69)	dB(A)	74
Pump type		Stainless Steel
Pump power	W	750
Pump capacity	l/min	400
Delivery head	m	11,5
Diameter of accessories	mm	38
Dimensions (LxWxH)	mm	500x620x1110
Weight	kg	32,0

STANDARD EQUIPMENT

PMDT00350 ACCESSORIES KIT FOR SUB Ø38 MM COMPOSED OF:

CODE: TBFX28237
FLEXIBLE HOSE 2,5 m
Ø38 mm



CODE: LAFN43048
ALUMINIUM/PLASTIC
TUBES 2X50 cm Ø38 mm



CODE: MPVR43047
HANDLE WITH AIR
REGULATOR Ø38 mm



CODE: SPPV43051
WET TOOL Ø38 mm

