



VACUUM CLEANERS - SPECIAL SOLUTIONS - FLOODED AREA EMPTYING

# GC 2/107 SUB+

POWER MAX

2400 W

WATER LIFT

2470 mmH<sub>2</sub>O

AIRFLOW

420 m<sup>3</sup>/h

TANK CAPACITY

107 l

## EXCLUSIVE FEATURES

- ▶ AP TUBE
- ▶ INNOVATIVE GASKET
- ▶ STRONG HOOKS
- ▶ INDEPENDENT MOTORS WITH LIGHT SWITCHES
- ▶ SEALANT FLOATER & INTEGRATED ANTIFOAM SYSTEM
- ▶ TIPPING TROLLEY
- ▶ RELIABLE CONSTRUCTION FOR INTENSIVE USE
- ▶ SUBMERSIBLE PUMP
- ▶ DOUBLE STAGE MOTORS



PUMP OUT

## MOST FREQUENTLY USE



## INNOVATIONS



## SPECS



HIGH EFFICIENCY STAINLESS STEEL SUBMERSIBLE PUMP FOR INDUSTRIAL APPLICATION



WATER FLOW VALVE



TIPPING TROLLEY

## TECHNICAL DATA

		<b>GC 2/107 SUB+</b>
Code		ASD015530
PERFORMANCE		
Usage		WET
Motor		2x2 stage
Power	W	2400 max
Voltage	V	220-240
Water lift	mmH <sub>2</sub> O	2470
Airflow	m <sup>3</sup> /h	420
Tank Capacity/Material	l	107/plastic (polyethylene)
Cable length	m	8,5
Sound Pressure Level (EN 60704-1; EN 60704-2-1; IEC 60335-2-69)	dB(A)	77
Pump type		Stainless Steel
Pump power	W	750
Pump capacity	l/min	400
Delivery head	m	11,5
Diameter of accessories	mm	38
Dimensions (LxWxH)	mm	500x620x1110
Weight	kg	32,0

## STANDARD EQUIPMENT

### PMDT00350 ACCESSORIES KIT FOR SUB Ø38 MM COMPOSED OF:

CODE: TBFX28237  
FLEXIBLE HOSE 2,5 m  
Ø38 mm



CODE: LAFN43048 (FOR 1 PC)  
ALUMINIUM/PLASTIC  
TUBE 50 cm Ø38 mm  
(MACHINE COMES WITH 2PCS)



CODE: MPVR43047  
HANDLE WITH AIR  
REGULATOR Ø38 mm



CODE: SPPV43051  
WET TOOL Ø38 mm

