







## **GS 1 MAXIBAG**

#### **EXCLUSIVE FEATURES**

- Þ **INNOVATIVE GASKET**
- STRONG HOOKS
- PCB PREFILTER
- TANGENTIAL OR METAL INLET
- **DOUBLE STAGE MOTORS AND TURBINE**
- **BIG AND BRAKED WHEELS**
- STARSHAPED FILTER, PCB PREFILTER AND ADDITIONAL CARTRIDGE
- LONGOPAC®

Code

- SELF DISCHARGE VALVE WITH BEST SEALING
- QUICK REPLACEMENT AND DETACHABLE SYSTEM
- PCB PREFILTER AND ADDITIONAL CARTRIDGE

ı	F		
ì		F	-
1	Ē	-	
\$			
n(l	A		



# **GS 3 MAXIBAG**

### **EXCLUSIVE FEATURES**

- **INNOVATIVE GASKET**
- STRONG HOOKS
- INDEPENDENT MOTORS WITH LIGHT SWITCHES
- **PCB PREFILTER**
- TANGENTIAL OR METAL INLET
- **DOUBLE STAGE MOTORS AND TURBINE**
- **BIG AND BRAKED WHEELS**
- STARSHAPED FILTER, PCB PREFILTER AND ADDITIONAL CARTRIDGE
- **LONGOPAC®**
- SELF DISCHARGE VALVE WITH BEST SEALING
- QUICK REPLACEMENT AND DETACHABLE SYSTEM
- PCB PREFILTER AND ADDITIONAL CARTRIDGE

		US S MANIDAU	
Code		ASD015121	
TECHNICAL DATA			
Usage		DRY	
Number of phases		single phase	
Voltage	V	220-240	
Frequency	Hz	50-60	
N. and type of motor		3x2 stages	
Power	W	2900-3300 max	
Water lift	mmH₂0	2470	
Airflow	m³/h	630	
Bag Capacity	m	20	
Diameter of inlet	mm	60	
Filtering surface	cm²	12.000	
Sound Pressure Level	dB(A)	76	
Dimensions (LxWxH)	mm	590x590x1120/1450	
Weight	Kg	44	

#### TECHNICAL DATA Usage DRY Number of phases single phase 220-240 Voltage 50-60 Frequency Hz N. and type of motor 1x2 stages W Power 1000-1200 max Water lift 2470 mmH<sub>2</sub>0 Airflow m3/h 210 **Bag Capacity** m 20 Diameter of inlet mm 60 Filtering surface $\,\text{cm}^2$ 12.000 Sound Pressure Level dB(A) 72 Dimensions (LxWxH) mm 590x590x1131/1460 Weight Kg 40

## STANDARD EQUIPMENT

CODE: FTDP00489 **POLYESTER CARTRIDGE** 12.000 cm





CODE: MISC00025

LONGOPACTM

CODE: FTDP00222 PREFILTER PCB



**GS 1 MAXIBAG** ASD011130



CODE: FTDP00489

CODE: PMDT00641



STANDARD EQUIPMENT



CODE: MISC00025

LONGOPACTM

CODE: FTDP00223 PREFILTER PCB

CC 3 MAYIRAC







