VACUUM CLEANERS - SPECIAL SOLUTIONS - HIGH REACH POINTS

KS 2/78 OPT FM SKYVAC INDUSTRIAL

POWER MAX	WATER LIFT	AIRFLOW	TANK CAPACITY
2400 W	3800 mmH_2O Flowmix On	220 m^3/h Flowmix On	78 l

EXCLUSIVE FEATURES

- INNOVATIVE GASKET
- INDEPENDENT MOTORS WITH LIGHT SWITCHES
- SEALANT FLOATER & INTEGRATED ANTIFOAM SYSTEM
- TIPPING TROLLEY
- RELIABLE CONSTRUCTION FOR INTENSIVE USE
- DETACHABLE TANK AND SOLID CART
- METAL TANGENTIAL INLET
- BIG WHEELS WITH BRAKES

MOST FREQUENTLY USE

HORECA
RETAIL
OFFICE
HEALTHCARE
EDUCATION
PHARMA INDUSTRY
CONSTRUCTION
HEAVY INDUSTRY

INNOVATIONS

LIGHTEST CARBON FIBER POLES

FLOWMIX

HIGH SPEED NEW GENERATION MOTORS

SPECS

SOLID CART WITH TIPPING TANK

FLOWMIX

CARTRIDGE PROTECTION

TECHNICAL DATA

		KS 2/78 SKYVAC INDUSTRIAL
Code		ASD015555
PERFORMANCE		
Usage		WET & DRY
Motor		2x1 stage
Power	W	2000-2400 max
Voltage	V	220-240
Water lift	mmH_2O	2470 FM OFF 3800 FM ON
Airflow	m^3/h	420 FM OFF 220 FM ON
Tank Capacity/Material	l	78/steel
Cable length	m	8,5
Sound Pressure Level (EN 60704-1; EN 60704-2-1; IEC 60335-2-69)	dB(A)	74
Diameter of flexible hose	mm	50
Dimensions (LxWxH)	mm	700x580 X1100
Weight	kg	42

STANDARD EQUIPMENT

CODE: FTDP44260
POLY CARTRIDGE

CODE: TBFX00820
FLEXIBLE HOSE 6 m Ø50 mm

CODE: KTRI04657
HOSE CUFF (FLEXI HOSE TO POLE)

OPTIONAL ACCESSORIES

Set up your vacuum cleaner with many other accessories (look at page 180-181)

Information about waterlift and airflow refers to single motors.
Specifications, descriptions and pictures are supplied as indicative: rights to technical modifications reserved without prior notice.

IP Cleaning Srl Viale Treviso 63 - 30026 Summaga di Portogruaro (VE) - Italy
Tel. +39 0421 205511 - Fax +39 0421 204227 | info@ipcworldwide.com - www.ipcworldwide.com