



## PLANET OIL 2M

## PLANET OIL 3M

### EXCLUSIVE FEATURES

- ▶ INDEPENDENT MOTORS WITH LIGHT SWITCHES
- ▶ DRAIN HOSE
- ▶ RELIABLE CONSTRUCTION FOR INTENSIVE USE
- ▶ DETACHABLE TANK AND SOLID CART
- ▶ TANGENTIAL OR METAL INLET
- ▶ DOUBLE STAGE MOTORS AND TURBINE
- ▶ BIG AND BRAKED WHEELS
- ▶ QUICK MAINTENANCE FRAMEWORK WITH DETACHABLE TANK
- ▶ SIEVE BASKET & ANTI BLOCK FLOATING SYSTEM
- ▶ ANTISKID WHEELS WITH BRAKES
- ▶ VISUAL FILLING INDICATOR
- ▶ SAFETY VALVES AND DRAIN SYSTEM
- ▶ INDUSTRIAL FRAMEWORK WITH AISI 304 WITH DETACHABLE TANK
- ▶ TANGENTIAL INLET AND CONVEYOR CONE
- ▶ VACUUM RELIEF VALVE AND FILTRATION LEVEL INDICATOR

	PLANET OIL 2M	PLANET OIL 3M
Code	ASID00523	ASID00524
<b>TECHNICAL DATA</b>		
Usage	WET & DRY	WET & DRY
Number of phases	single phase	single phase
Voltage	220-240	220-240
Frequency	50-60	50-60
N. and type of motor	2x2 stages	3x2 stages
Power	2000-2400 max	3000-3600 max
Water lift	2470	2470
Airflow	420	630
Tank Capacity	100	100
Bucket sieve capacity	40	40
Diameter of inlet	60	60
Sound Pressure Level	74	76
Dimensions (LxWxH)	850x650x1350	850x650x1350
Weight	62	65

### STANDARD EQUIPMENT

CODE: KTRI02521  
FILTERING KIT (3100 + 1500 cm<sup>2</sup>)

CODE: FTC000011  
NYLON FILTER (PA 200 μ)

CODE: SECC00113  
BUCKET SIEVE



### OPTIONAL ACCESSORIES

Optional Anti-oil tool kit Ø50-60 mm

PMDT00449