



HOT WATER WEED REMOVAL SYSTEM

# GREEN JET

PRESSURE

8  
bar

FLOW RATE

600  
l/h

ABSORBED POWER

0,8  
kW

## EXCLUSIVE TECHNOLOGIES

- ▶ DELAYED TOTAL STOP - DTS
- ▶ INTELLIGENT AUTOMATIC SWITCH OFF - IASF
- ▶ DRY RUNNING PROTECTION - DRP
- ▶ LIMESCALE/CORROSION PROTECTION UNIT - LCPU
- ▶ ANTISCALE LEVEL CONTROL - ALC
- ▶ INFRARED FLAME CONTROL SYSTEM - FCS
- ▶ MAINTENANCE CHECK LED - MCL



## MOST FREQUENTLY USE

AGRICULTURE



PUBLIC WORKS



MUNICIPALITIES



## INNOVATIONS



MSCT<sup>™</sup>  
MULTIFUNCTION  
SAFETY  
CONTROL



M421  
ANTI-SCALE



MODULAR  
BUILD-UP



IPC'S  
EXCLUSIVE  
BOILER

## SPECS



STANDARD LIFTING HOOK TO BE RAISED AND TRANSPORTED ANYWHERE



POWER SUPPLY FROM THE WATER TANK OR EXTERNAL NETWORK



COMPLETE CONTROL PANEL TO MONITOR MACHINE FUNCTIONS

## TECHNICAL DATA

### GREEN JET 1010 M

Codice		GNVA40051
Operating pressure	bar/Mpa	8/0,8
Flow rate	l/h	600
Outlet water temperature max	°C	~100
Power supply	Ph-V-Hz	1-220-50
Absorbed power	kW	0,8
Motor power	kW	0,55
Remote control		DTS
Pump (type)	IPC volumetric rotary vane pump is self-priming, high-performance. The pump body is brass made	
Boiler thermal power	kW	74
Fuel consumption	Kg/h	6,24
Fuel tank	l	16
Antiscale tank	l	2
Dimension (LxWxH)	Cm	100x80x103
Weight	Kg	112

## STANDARD EQUIPMENT

CODE: IPPR40027  
HANDGRIP ML330 +  
EXTENSION 350 mm



CODE: LCLC40025  
LANCE WITH SPRAY BAR



CODE: TBAP39122  
H.P. HOSE 20 m (NON  
MARKING RUBBER HOSE)

