



AUTOMATIC SCRUBBERS - RIDER

CT110

The CT110 is a very compact rider, but with a 29/32 gallon tank it offers much higher productivity than other rider scrubbers in its range. This unit is designed to offer high performance with very little training required.

MAX PRODUCTIVITY

27,000-
45,000 ft²/h

BATTERIES
RUNNING TIME

2.3-3.0 h

KEY SPECS

29 gal
28", 32" rider

MOST FREQUENT USE



INTUITIVE CONTROL PANEL



INTEGRATED CHEM DOSE



EASY MAINTENANCE



INNOVATIONS




CONSTANT CLEANING PERFORMANCE

ELECTRONIC SYSTEM



INNOVATION



SELF-LEVELLING SYSTEM

DETAILS

· The brush pressure with self-leveling and self-adjusting head, allows a perfect fit between the brush and floor

· System available as mechanical, electro mechanical or electronic according to machine models

MACHINES

· Available on all machines models

CT110

EASY TO HANDLE

Design to be specifically easy to operate and built with an ergonomic, comfortable design.



BRUSH

Spin-on spin-off brush pad driver (single brush only)

TILTABLE TANK

Large solution capacity in a minimum external space

SQUEEGEE

Squeegee system designed to absorb harsh impact

Other Features

- (CFS) Central Flow System solution distribution from brush center
- Great maneuverability with its optimum weight distribution
- Designed to assure minimum noise levels
- Easy to use control panel
- Automatic stop (by pedal release) in working mode
- Battery level indicator
- Solution tank discharge hose
- Anti Foam System
- Brush replacement without tools
- Squeegee blades can be used on four sides before replacement
- Automatic squeegee lift in reverse
- Squeegee assembly without tools
- Easy access to internal compartments
- Oil bath gear reduction box

CT110 TECHNICAL SPECIFICATIONS

		CT110	CT110
Code		CT110 BT70	CT110 BT85
PRODUCTIVITY			
Max theoretical productivity	ft ² /h - m ²	27,000 ft ² /2,508 m ²	45,000 ft ² /5,525 m ²
Cleaning path	in/mm	28 in/ 700 mm	32 in/ 850 mm
Squeegee Width	in/mm	40 in/ 1010 mm	40 in/ 1010 mm
Water tank capacity	Gal/ l	29 gal/ 110 l	29 gal/ 110 l
Max running time	min	180	180
Voltage	V-Ah	24V (4x6)	24V (4x6)
Installed power	W	550	550
Max Speed		3.9 mph/ 6.5 kmh	3.9 mph/ 6.5 kmh
Brush pressure	lbs/ kg	99 lbs/ 45 kg	132 lbs/ 60 kg
Weight	lbs/ kg	471 lbs/ 214 kg	509 lbs/ 232 kg
Dimensions	in	59 x 30 x 50 in	59 x 34 x 50 in

AVAILABLE ACCESSORIES

<p>PAD DRIVER SPPV01228 (2 -14") SPPV01234 (2- 16")</p> 	<p>NYLON BRUSH SPPV01472 (2 -14") SPPV01516, SPPV01527 (2-16")</p> 	<p>TYNEX BRUSH SPPV01475 (2-14") SPPV01517, SPPV00437 (2-16")</p> 	<p>6V 240 AH 12V240</p> 	<p>6V 225 AGM 6V225-AGM</p> 	<p>CHARGER WET/ GEL BACA00136</p> 
<p>ON-BOARD CHARGER KTRI01709</p> 	<p>BATTERY WATERING SYSTEM CR-BWS-F-4</p> 	<p>MICROFIBER PAD DRIVER SPPV01259</p> 	<p>MICROFIBER SCRUB PAD SPPV01260</p> 	<p>MICROFIBER SOFT & SHINE PADS SPPV01261, SPPV01263</p> 	<p>DIAMOND PADS ECS211668, ECS211666, ECS212520, ECS211667, ECS211700</p> 
<p>DIAMOND PAD DRIVER SPPV01275</p> 	<p>CHEM DOSE KIT KTRI01711</p> 	<p>FLASHING BEACON KTRI01710</p> 	<p>SQUEEGEES (CT110 BT70) PMVR02239 (COMPLETE) MPVR08040 (FRONT) MPVR08036 (REAR)</p> 	<p>SQUEEGEES (CT110 BT85) PMVR02243 (COMPLETE) MPVR08041 (FRONT) MPVR08037 (REAR)</p> 	

GET RIGHT SIZED

	Description	Continuous run-time	Theoretical ft ² / h	Maximum Theoretical ft ² /charge	Ft ² charge efficiency (70%)
CT110BT70	Rider 240ah Battery	3.0 h	38,981	116,944	81,861
CT110BT70	Rider, 225 AGM Battery	3.0 h	38,981	116,944	81,861
CT110BT85	Rider, 240ah Battery	3.0 h	44,550	133,650	93,555
CT110BT85	Rider, 225 AGM Battery	3.0 h	44,550	133,650	93,555



IPC Eagle Corporation
12450 Oliver Ave S Burnsville, MN 55337

800-486-2775
info@ipceagle.com