



IPC

BY TENNANT COMPANY

SCRUBBER DRYERS - WALK BEHIND

CT40

The CT40 is a compact scrubber with a large tank capacity. Its ease of use will offer high productivity and performance, while requiring very little effort for the operator.

MAX PRODUCTIVITY

17,000-
19,000
ft²/h

BATTERY RUNNING TIME

2.0-3.5 h

KEY SPECS

11/13 gal
20" brush or
traction drive



CERTIFICATIONS



GREEN CLEANING
EFFICIENCY



ISO 14067 CARBON
FOOTPRINT CERTIFIED

BATTERY CHARGER INCLUDED

MOST FREQUENT USE

RETAIL



HOSPITAL



CLEANING CONTRACTORS



MUNICIPALITIES



INNOVATIONS



SLS™
SELF
LEVELING
SYSTEM



YELLOW
TOUCH POINTS


SPECS



INTUITIVE CONTROL PANEL



SEPARATE DETERGENT DOSING
SYSTEM. (OPTIONAL)



ANTI-FOAM SYSTEM WITH
SPECIAL ELECTROMECHANICAL
SUCTION MOTOR PROTECTION

TECHNICAL DATA

		CT40 B50	CT40 BT50
Code			
PERFORMANCE			
Max theoretical productivity	ft²/h	17,000	19,000
Cleaning path	in	20	20
Water tank capacity (solution recovery)	l	10/13	10/13
Max running time	min	210	210
Voltage	V	24(2x12)	24(2x12)
Installed power	W	550	550
Brush pressure	lbs	51	51
Squeegee width	in	32	32
Max speed	mph	2.2	2.2
Weight	lbs	183	183
Dimension (LxWxH)	iN	48x20x38	48x20x38

STANDARD EQUIPMENT

		CT40 B50	CT40 BT50
BRUSHES			
PPL SOFT		SPPV01498	SPPV01498
SQUEEGEE BLADES			
LATEX FRONT BLADE		MPVR08039 - 880mm	MPVR08039 - 880mm
LATEX REAR BLADE		MPVR08035 - 900mm	MPVR08035 - 900mm

ACCESSORIES

BRUSHES



PADS/SUPER PADS



SQUEEGEE BLADES



CHEM DOSE KIT



SOLUTION TANK DRAIN AND LEVEL HOSE KIT



SPLASH GUARD



DISCHARGE HOSE

