



**IPC**

BY TENNANT COMPANY

**AUTOMATIC SCRUBBERS - RIDERS**

# CT80

The CT80 is one of the smallest rider scrubbers on the market and is able to fit through spaces that typical rider scrubbers cannot. It is able to drive through door frames, in smaller spaces such as hallways all while being able to be operated in a comfortable ride-on design.

**MOST FREQUENT USE**

**RETAIL**




**HOSPITALITY**



**CLEANING CONTRACTORS**



**EDUCATION**



4 BATTERIES FOR LONG RUN-



PRESET WORKING PROGRAMS



CHEM DOSE OPTIONAL

**MAX PRODUCTIVITY**

19,000-  
27,000 ft<sup>2</sup>/h

**BATTERY  
RUNNING TIME**

3.7 h

**KEY SPECS**

20/21 gal

21", 24" 28" rider



**INNOVATIONS**



SLST<sup>™</sup>  
SELF  
LEVELING  
SYSTEM



ECO  
SELECT



YELLOW  
TOUCH  
POINTS

		CT80 BT55 RIDER	CT80 BT60 RIDER	CT80 BT70 RIDER
Max theoretical productivity	ft <sup>2</sup> /h - m <sup>2</sup> /h	19,000 ft <sup>2</sup> / 1,765 m <sup>2</sup>	23,000 ft <sup>2</sup> / 2,136 m <sup>2</sup>	27,000 ft <sup>2</sup> / 2, 880 m <sup>2</sup>
Cleaning path	in / mm	21"/ 610 mm	24"/ 610 mm	28"/ 710 mm
Water tank capacity (solution recovery)	gal/ l	21/22 gal - 78/80 l	21/22 gal - 78/80 l	21/22 gal - 78/80 l
Max running time	min	240	240	240
Voltage	V	24 (4 x 6)	24 (4 x 6)	24 (4 x 6)
Installed power	W	480	480	480
Squeegee width	in/ mm	37 in/ 942 mm	37 in/ 942 mm	37 in/ 942 mm
Max speed	mph/ kph	2.2 mph/ 3.5 kph	2.2 mph/ 3.5 kph	2.2 mph/ 3.5 kph
Weight (w/o batteries)	lbs/ kg	420 lbs/ 190 kg	437 lbs/ 198 kg	480 lbs/ 217 kg
Dimensions (L x W x H)	in/ mm	52 x 26 x 41 in	52 x 27 x 41 in	52 x 30 x 41 in
Noise level	dB	65 dB	65 dB	65 dB