

SWEEPERS - WALK BEHIND

505

MAX PRODUCTIVITY

MAIN BRUSH PATH

VOLTAGE SYSTEM

 $2450 \, \text{m}^2/\text{h}$ $500 \, \text{mm}$ $12 \, \text{v}$



BATTERIES AND BATTERY CHARGER NOT INCLUDED

MOST FREQUENTLY USE

INNOVATIONS

RETAIL

CLEANING SURFACE





CLEANING CONTRACTORS

MUNICIPALITIES

SPECS







LARGE FRONTAL WASTE TRAY



EASY MAINTENANCE

TECHNICAL DATA		
		505 ET
Code		MSUT00695
PERFORMANCE		
Main brush cleaning path width	mm	500
Side brush cleaning path width	mm	700
Max theoretical productivity	m²/h	2450
Voltage	V-Ah	12
Installed power	W/HP	485
Hopper capacity	l	65
Hopper discharge system	Type/mm	Low-Manual
Filtering surface	m^2	3
Fylter type		Panel-paper
Max speed	km/h	3,5
Max Climb	%	2
Weight without batteries	kg	75
Dimension (LxWxH)	mm	1160X810X1000

STANDARD ACCESSORIES	505 ET	
BRUSHES	30311	
MAIN BRUSH	SPPV00051	
SIDE BRUSH	SPPV76057	
FILTERS		
FILTER	FTDP76065	

BATTERIES AND BATTERY CHARGERS

BATTERIES	N°	CHARACTERISTIC	DIMENSION	RUNNING TIME	BATTERY CHARGERS
Acid flat plate battery BAAC00011	1	12V 60 Ah (C5)	278x175x190	70	Stand alone high frequency BLS010 - BACA00133 Stand alone low frequency 12V 10Ah -BACA00001
Acid flat plate battery BAAC00012 *	1	12V 75 Ah (C5)	325x175x212	90	Stand alone high frequency BLS010 - BACA00133 Stand alone low frequency 12V 10Ah -BACA00001

^{*} RECOMMENDED WITH MPVR00610