



IPC

BY TENNANT COMPANY

SCRUBBER DRYERS - WALK BEHIND

CT30



MAX PRODUCTIVITY

1575 m²/h

BATTERIES RUNNING TIME

2,5 h
1,5 h eco version

WATER TANK RUNNING TIME

45'
working session



TELEMATICS GPS (opt)

GEOLOCATION OF
ALL YOUR MACHINES



CERTIFICATIONS



GREEN CLEANING
EFFICIENCY



ISO 14067 CARBON
FOOTPRINT CERTIFIED

BATTERIES AND BATTERY CHARGER INCLUDED

MOST FREQUENTLY USE

RETAIL



HORECA



CLEANING CONTRACTORS



MUNICIPALITIES



INNOVATIONS



ECO
SELECT



TELEMATICS
GPS



DBL™
DOUBLE
BATTERY
LIFE



SLS™
SELF
LEVELING
SYSTEM



BACTERIA
CONTROL



ANTIBACTERIAL
PLASTIC

SPECS



FOLDABLE HANDLE



PRESET WORKING
PROGRAMS



THREE STAGE VACUUM MOTOR

TECHNICAL DATA

Code		CT30 B45 LPTB02435	CT30 C45 LPTE00531	CT30 B45 ECO LPTB01523	CT30 B45 ANTIBACTERIAL LPTB03421
PERFORMANCE					
Max theoretical productivity	m²/h	1575	1575	1575	1575
Cleaning path	mm	460	450	460	460
Water tank capacity (solution recovery)	l	28/30	28/30	28/30	28/30
Max running time	min	150	Unlimited	150	150
Voltage	V-Ah	24(2x12)-74 AGM	230-50/60	24(2x12)-50 AGM	24(2x12)-74 AGM
Installed power	W	900	700	900	900
Brush pressure	kg	17/21	17/21	17/21	17/21
Squeegee width	mm	550	550	550	550
Max speed	km/h	3,5	3,5	3,5	3,5
Weight	kg	98	53	98	98
Dimension (LxWxH)	mm	850x550x1220	850x550x1220	850x550x1220	960x550x1220

STANDARD ACCESSORIES

	CT30 B45	CT30 C45	CT30 B45 ECO	CT30 B45 ANTIBACTERIAL
BRUSHES				
PPL MEDIUM	SPPV02665	SPPV02665	SPPV02665	SPPV02665
SQUEEGEE BLADES				
LATEX FRONT BLADE	MPVR05953 - 660mm	MPVR05953 - 660mm	MPVR05953 - 660mm	MPVR05953 - 660mm
LATEX REAR BLADE	MPVR05954 - 715mm	MPVR05954 - 715mm	MPVR05954 - 715mm	MPVR05954 - 715mm

CONSUMABLES (Codes available on price list)


BRUSHES



PADS/SUPER PADS



SQUEEGEE BLADES



OPTIONAL ACCESSORIES

CODE: MPVR05966
SPLASH GUARD



CODE: KTRI02257
EXTERNAL SUCTION KIT



CODE: KTRI02084
REAR HD SQUEEGEE KIT



CODE: PRCH00578
**BIOSAN RAPIDE WT
(30PCS/30DAYS)**



CODE: KTRI06219
KIT TELEMATIC BASIC



BATTERIES AND BATTERY CHARGERS

BATTERIES	N°	CHARACTERISTICS	DIMENSION	RUNNING TIME	BATTERY CHARGERS
IPC AGM battery BAAC00117	2	12V 74 Ah (C5)	257x172x212	150 min	On board battery charger 24V 10Ah KTRI02245
EXIDE gel battery BAAC00124	2	12V 63 Ah (C5)	261x171x210	130 min	On board battery charger 24V 10Ah KTRI02245
AGM battery (only Eco) BAAC00134	2	12V 50 Ah (C5)	229x138x212	90 min	On board battery charger 24V 5 Ah KTRI02244

RECOMMENDED BATTERIES AND BATTERY CHARGER