



SCRUBBER DRYERS - WALK BEHIND

CT55

MAX PRODUCTIVITY

2700 m²/h

BATTERIES RUNNING TIME

2,5 h

WATER TANK RUNNING TIME

60'
working session



TELEMATICS GPS [optional]

GEOLOCATION OF
ALL YOUR MACHINES



BATTERIES AND BATTERY CHARGER NOT INCLUDED

MOST FREQUENTLY USE

RETAIL



HORECA



CLEANING CONTRACTORS



MUNICIPALITIES



INNOVATIONS



TELEMATICS
GPS



DBL
DOUBLE
BATTERY
LIFE



SLS
SELF
LEVELING
SYSTEM

SPECS



INTUITIVE CONTROL PANEL



SEPARATE DETERGENT
DOSING SYSTEM (OPTIONAL)



ANTI-FOAM SYSTEM WITH
SPECIALELECTROMECHANICAL
SUCTION MOTOR PROTECTION

TECHNICAL DATA

Code		CT55 B55 LPTB01516	CT55 BT55 LPTB01517	CT55 C55 LPTE01102
PERFORMANCE				
Max theoretical productivity	m ² /h	1.925	2.475	1.925
Cleaning path	mm	550	550	550
Water tank capacity (solution recovery)	l	55/60	55/60	55/60
Max running time	min	150	140	Unlimited
Voltage	V-Ah	24(2x12)-105 GEL	24(2x12)-105 GEL	230-50
Installed power	W	1.030	1.230	1.100
Brush pressure	kg	18	18	25
Squeegee width	mm	815	815	815
Max speed	km/h	4	5	5
Weight (Without Batteries)	kg	68	84	91
Dimension (LxWxH)	mm	1190x685x1018	1190x685x1018	1190x640x1018

STANDARD EQUIPMENT

	CT55 B55	CT55 BT55	CT55 C55
BRUSHES			
PPL SOFT	SPPV01505	SPPV01505	SPPV01505
CYLINDRICAL BRUSH - PPL SOFT Ø 0,3 mm	-	-	-
SQUEEGEE BLADES			
LATEX FRONT BLADE	MPVR08039 - 880mm	MPVR08039 - 880mm	MPVR08039 - 880mm
LATEX REAR BLADE	MPVR08035 - 900mm	MPVR08035 - 900mm	MPVR08035 - 900mm

CONSUMABLES (Codes available on price list)

BRUSHES



PADS



SQUEEGEE BLADES



OPTIONAL ACCESSORIES

CODE: MECB42513

MAIN CABLE M/F
SOCKET - 20 m
[3X2,5mm 2 230V - 50HZ]



CODE: KTRI02141

CHEM DOSE KIT



CODE: MPVR05611

SPLASH GUARD



CODE: KTRI01573

DISCHARGE HOSE



CODE: KTRI01870

SOLUTION TANK DRAIN
AND LEVEL HOSE KIT



CODE: KTRI02257

EXTERNAL SUCTION KIT



CODE: KTRI06169

KIT TELEMATIC BASIC
FOR B VERSIONS
(NO TRACTION)



CODE: KTRI06167

KIT TELEMATIC BASIC
FOR BT VERSIONS
(WITH TRACTION)



CODE: KTRI06168

KIT TELEMATIC FULL
FOR B VERSIONS
(NO TRACTION)



CODE: KTRI06166

KIT TELEMATIC FULL
FOR BT VERSIONS
(WITH TRACTION)



BATTERIES AND BATTERY CHARGERS

BATTERIES	N°	CHARACTERISTICS	DIMENSION	RUNNING TIME	BATTERY CHARGERS
IPC gel battery BAAC00105	2	12V 105 Ah (C5)	345x170x285	150 min	On board battery charger 24V 10 Ah- KTRI01703 Stand alone high frequency BLS010 - BACA00133
EXIDE gel battery BAAC00024	2	12V 105 Ah (C5)	345x174x283	150 min	On board battery charger 24V 10 Ah- KTRI01703 Stand alone high frequency BLS010 - BACA00133
Acid tubular plate BAAC00136	2	12V 85 Ah (C5)	308x175x225	160 min	On board battery charger 24V 10 Ah- KTRI01703 Stand alone high frequency BLS010 - BACA00133 Stand alone low frequency 24V 12 Ah BACA00060
Dry charge flate plate BAAC00009	2	12V 105 Ah (C5)	261x171x210	160 min	On board battery charger 24V 10 Ah- KTRI01703 Stand alone high frequency BLS010 - BACA00133 Stand alone low frequency 24V 12 Ah BACA00060
Acid tubular plate BAAC00070	2	12V 118 Ah (C5)	345x170x285	160 min	On board battery charger 24V 10 Ah- KTRI01703 Stand alone high frequency BLS010 - BACA00133 Stand alone low frequency 24V 12 Ah BACA00060

RECOMMENDED BATTERIES AND BATTERY CHARGER