



IPC

BY TENNANT COMPANY

CT80 LI-ION



LI-ION
BATTERY



		CT80 BT55 BATTERY - EXTERNAL CHARGER INCLUDED	CT80 BT55 BATTERY - ON BOARD CHARGER INCLUDED	CT80 BT55 BATTERY - EXTERNAL CHARGER INCLUDED
Code		LPTB03765	LPTB03701	LPTB03767
PERFORMANCE				
Max theoretical productivity	m²/h	3180	3180	4070
Cleaning path	mm	550	550	700
Water tank capacity (solution recovery)	l	80/83	80/83	80/83
Productivity for shift	m²	up to 2475	up to 2475	up to 3150
Voltage	V-Ah	25,6V -3 X 50 Ah Lithium	25,6V -1 X 90 Ah Lithium	25,6V -2 X 90 Ah Lithium
Max running time	min	170	150	270
Battery Charging Time - On Board Charger	Hrs	-	6	-
Battery Charging Time - External Charger	Hrs	2,5	-	2
Battery Life	Cycles	4000	4000	4000
Installed power	W	1200	1200	1600
Brush pressure	kg	22	22	50
Squeegee width	mm	710	710	942
Max speed	km/h	6	6	6
Weight (Without Batteries)	kg	118	118	145
Dimension (L xWxH)	mm	1310x673x1030	1310x673x1030	1310x760x1030



		CT80 BT70 BATTERY - EXTERNAL CHARGER INCLUDED	CT80 BT70 BATTERY - ON BOARD CHARGER INCLUDED	CT80 BT70 BATTERY - EXTERNAL CHARGER INCLUDED
Code		LPTB03766	LPTB03702	LPTB03768
PERFORMANCE				
Max theoretical productivity	m²/h	4070	4070	4070
Cleaning path	mm	700	700	700
Water tank capacity (solution recovery)	l	80/83	80/83	80/83
Productivity for shift	m²	up to 3150	up to 3150	up to 3150
Voltage	V-Ah	25,6V - 3 X 50 Ah Lithium	25,6V - 2 X 90 Ah Lithium	25,6V - 2 X 90 Ah Lithium
Max running time	min	180	270	180
Battery Charging Time - On Board Charger	Hrs	-	7	-
Battery Charging Time - External Charger	Hrs	2,5	-	2
Battery Life	Cycles	4000	4000	4000
Installed power	W	1600	1600	1600
Brush pressure	kg	50	50	50
Squeegee width	mm	942	942	942
Max speed	km/h	6	6	6
Weight (Without Batteries)	kg	145	145	145
Dimension (LxWxH)	mm	1310x760x1030	1310x760x1030	1310x760x1030