



IPC

BY TENNANT COMPANY

HOT WATER GENERATOR

FIRE BOX

PRESSURE

175÷350
bar

FLOW RATE

1260 l/h

ABSORBED POWER

0,3 kW



EXCLUSIVE CHARACTERISTICS

- BOILER IGNITION DELAY - IBD

MOST FREQUENTLY USE

AUTOMOTIVE



AGRICULTURE



CONSTRUCTION INDUSTRY



MUNICIPALITIES



HEAVY INDUSTRY



SPECS



SINGLE PHASE BURNER
MOTOR CONNECTED TO FAN
AND DIESEL FUEL PUMP



COVER AND TROLLEY IN
PAINTED SHEET METAL



ELECTRIC CONTROL PANEL
WITH ON-OFF SWITCH AND
THERMOSTAT

TECHNICAL DATA

		30M FIRE BOX	40M FIRE BOX	40/350 FIRE BOX
Code		CDVE49715	CDVE49716	CDVE40027
PERFORMANCE				
Operating pressure max	bar/Mpa	175/17,5	200/20	350/35
Flow rate	l/h	360-1260	360-1260	360-1260
Outlet water max. temperature	°C	140	140	140
Power supply	Ph-V-Hz/A	1-230-50/2	1-230-50/2	1-230-50/2
Absorbed power	kW	0,3	0,3	0,3
Fuel tank	l	18	18	18
Fuel consumption max	kg/h	5,8	7,2	7,2
Boiler thermal power	kW	70	90	90
Dimension (LxWxH)	cm	120x70x100	120x70x100	120x70x100
Weight	kg	102,3	118,8	118,8

STANDARD EQUIPMENT

CODE: RCIN03755
HOSE COUPLINGS



CODE: TBAP29050
HIGH PRESSURE HOSE
L2310 R2 3/8F - 3/8F

