

#### **VACUUM CLEANERS - SPECIAL SOLUTIONS - FLOODED AREA EMPTYING**

# GC 2/90 SUB

**POWER MAX** 

WATER LIFT

**AIRFLOW** 

**TANK CAPACITY** 

2400 2470 420

mmH<sub>2</sub>O



#### **EXCLUSIVE FEATURES**

- **AP TUBE**
- **INNOVATIVE GASKET**
- **STRONG HOOKS**
- **INDEPENDENT MOTORS** WITH LIGHT SWITCHES
- **SEALANT FLOATER & INTEGRATED ANTIFOAM SYSTEM**
- RELIABLE CONSTRUCTION **FOR INTENSIVE USE**
- SUBMERSIBLE PUMP
- **DOUBLE STAGE MOTORS**

# **MOST FREQUENTLY USE**

**AGRICULTURE** 

CONSTRUCTION

**HARDWARE CUSTOMER** 

**HEAVY INDUSTRY** 

**AUTOMOTIVE** 

# **INNOVATIONS**



#### **SPECS**



PROFESSIONAL SUBMERSIBLE **PUMP** 



WATER FLOW VALVE



OPTIONAL FIX SQUEEGEE

#### **TECHNICAL DATA**

		GC 2/90 SUB
Code		ASD015106
PERFORMANCE		
Usage		WET
Motor		2x2 stage
Power	W	2400 max
Voltage	V	220-240
Water lift	mmH <sub>2</sub> O	2470
Airflow	m³/h	420
Tank Capacity/Material	l	90/plastic (polyethylene)
Cable length	m	8,5
Sound Pressure Level (EN 60704-1; EN 60704-2-1; IEC 60335-2-69)	dB(A)	77
Pump type		Plastic
Pump power	W	370
Pump capacity	l/min	180
Delivery head	m	7
Diameter of accessories	mm	38
Dimensions (LxWxH)	mm	450x500x950
Weight	kg	26,0

#### STANDARD EQUIPMENT

### PMDT00350 ACCESSORIES KIT FOR SUB Ø38 MM COMPOSED OF:

CODE: TBFX28237 FLEXIBLE HOSE 2,5 m Ø38 mm



CODE: LAFN43048 (FOR 1 PC)
ALUMINIUM/PLASTIC
TUBE 50 cm Ø38 mm
(MACHINE COMES WITH 2PCS)



CODE: SPPV43051 WET TOOL Ø38 mm







#### **OPTIONAL ACCESSORIES**



To connect to water flow valve

