



IPC

BY TENNANT COMPANY

VACUUM CLEANERS - SPECIAL SOLUTIONS - FLOODED AREA EMPTYING

GC 2/90 SUB

POWER MAX

2400
W

WATER LIFT

2470
mmH₂O

AIRFLOW

420
m³/h

TANK CAPACITY

90
l



PUMP
OUT

EXCLUSIVE FEATURES

- ▶ AP TUBE
- ▶ INNOVATIVE GASKET
- ▶ STRONG HOOKS
- ▶ INDEPENDENT MOTORS WITH LIGHT SWITCHES
- ▶ SEALANT FLOATER & INTEGRATED ANTIFOAM SYSTEM
- ▶ RELIABLE CONSTRUCTION FOR INTENSIVE USE
- ▶ SUBMERSIBLE PUMP
- ▶ DOUBLE STAGE MOTORS

MOST FREQUENTLY USE

AGRICULTURE



CONSTRUCTION



HARDWARE CUSTOMER



HEAVY INDUSTRY



AUTOMOTIVE



INNOVATIONS



BLACK IS GREEN™



NEW BLEND FLEXIBLE HOSE

SPECS



PROFESSIONAL SUBMERSIBLE PUMP



WATER FLOW VALVE



OPTIONAL FIX SQUEEGEE

TECHNICAL DATA

		GC 2/90 SUB
Code		ASD015106
PERFORMANCE		
Usage		WET
Motor		2x2 stage
Power	W	2400 max
Voltage	V	220-240
Water lift	mmH ₂ O	2470
Airflow	m ³ /h	420
Tank Capacity/Material	l	90/plastic (polyethylene)
Cable length	m	8,5
Sound Pressure Level (EN 60704-1; EN 60704-2-1; IEC 60335-2-69)	dB(A)	77
Pump type		Plastic
Pump power	W	370
Pump capacity	l/min	180
Solids diameter for pumping out	mm	20 max
Delivery head	m	7
Diameter of accessories	mm	38
Dimensions (LxWxH)	mm	450x500x950
Weight	kg	26,0

STANDARD EQUIPMENT

CODE: TBFX01277

**EXTRA STRONG FLEXIBLE
HOSE 5 m Ø38 mm**



CODE: LAFN43048 (FOR 1 PC)

**ALUMINIUM/PLASTIC
TUBE 50 cm Ø38 mm**
(MACHINE COMES WITH 2PCS)



CODE: MPVR43047

**HANDLE WITH AIR
REGULATOR Ø38 mm**



CODE: SPPV43051

WET TOOL Ø38 mm



OPTIONAL ACCESSORIES

CODE: TBBP00719

**ANTIFREEZE HOSE 5 m
Ø30 mm**



CODE: FSVR00129

HOSE CLAMP 30X45



CODE: PMVR06680

DFS POLY KIT



To connect to water flow valve



OPTIONAL SQUEEGEE KIT
CODE: KTRI05342

**INCREASE PRODUCTIVITY
RECOVERING LIQUIDS ON WIDE
SURFACES.**



EASY TO ASSEMBLY
Check out the tutorial
video to know more!