

VACUUM CLEANERS - SPECIAL SOLUTIONS - FLOODED AREA EMPTYING

GC 2/90 SUB

POWER MAX

WATER LIFT

AIRFLOW

TANK CAPACITY

2400

2560 mmH_2O

EXCLUSIVE FEATURES

- **NEW 5-METER SUPER STRONG FLEX HOSE**
- **AP TUBE**
- **INNOVATIVE GASKET**
- **STRONG HOOKS**
- **INDEPENDENT MOTORS** WITH LIGHT SWITCHES
- **SEALANT FLOATER & INTEGRATED ANTIFOAM SYSTEM**
- **RELIABLE CONSTRUCTION FOR INTENSIVE USE**
- SUBMERSIBLE PUMP



MOST FREQUENTLY USE

AGRICULTURE







CONSTRUCTION

HARDWARE CUSTOMER

HEAVY INDUSTRY

AUTOMOTIVE

SPECS



PROFESSIONAL SUBMERSIBLE **PUMP**



WATER FLOW VALVE



OPTIONAL FIX SQUEEGEE

TECHNICAL DATA

		GC 2/90 SUB
Code		ASD015106
PERFORMANCE		
Usage		WET
Motor		2
Power	W	2000-2400 max
Voltage	V	220-240
Water lift	mmH₂0	2560
Airflow	m³/h	504
Tank Capacity/Material	l	90/plastic (polyethylene)
Cable length	m	8,5
Sound Pressure Level (EN 60704-1; EN 60704-2-1; IEC 60335-2-69)	dB(A)	77
Pump type		Plastic
Pump power	W	370
Pump capacity	l/min	180
Solids diameter for pumping out	mm	20 max
Delivery head	m	7
Diameter of accessories	mm	38
Dimensions (LxWxH)	mm	450x500x950
Weight	kg	26,0

STANDARD EQUIPMENT

CODE: TBFX01277

EXTRA STRONG FLEXIBLE
HOSE 5 m Ø38 mm

CODE: LAFN43048 (FOR 1 PC)
ALUMINIUM/PLASTIC
TUBE 50 cm Ø38 mm
(MACHINE COMES WITH 2PCS)

CODE: MPVR43047

HANDLE WITH AIR

REGULATOR Ø38 mm

CODE: SPPV43051 WET TOOL Ø38 mm









OPTIONAL ACCESSORIES



To connect to water flow valve

