



HOT WATER WEED REMOVAL SYSTEM



# GREEN JET 7510

PRESSURE

75  
bar

FLOW RATE

600  
l/h

ABSORBED POWER

1,9  
kW

## EXCLUSIVE TECNOLOGIES

- ▶ DELAYED TOTAL STOP - DTS
- ▶ INTELLIGENT AUTOMATIC SWITCH OFF - IASF
- ▶ DRY RUNNING PROTECTION - DRP
- ▶ LIMESCALE/CORROSION PROTECTION UNIT - LCPU
- ▶ ANTISCALE LEVEL CONTROL - ALC
- ▶ INFRARED FLAME CONTROL SYSTEM - FCS
- ▶ MAINTENANCE CHECK LED - MCL



## SPECIAL APPLICATIONS - CLEANING, WASHING AND WEED CONTROL WITH ONE MACHINE

## MOST FREQUENTLY USE

AGRICULTURE

PUBLIC WORK

MUNICIPALITIES

## INNOVATIONS



MSCM<sup>TM</sup>  
MULTIFUNCTION  
SAFETY  
CONTROL



M421  
ANTI-SCALE



MODULAR  
BUILD-UP



IPC'S  
EXCLUSIVE  
BOILER

## SPECS



2 FIXED PNEUMATIC WHEELS AND 2 PIVOT WHEELS (1 WITH BREAK)



DIRECT WATER SUPPLY OR SUCTION WITH EXTERNAL TANK



CONTROL PANEL SHOWING: BURNER LOCKOUT INDICATOR LIGHT, WARNING LACK OF ANTISCALE, SCHEDULED MAINTENANCE (150 HRS), MAX TEMPERATURE INDICATOR (TEMPERATURE REACHED).

## TECHNICAL DATA

			<b>GREEN JET 7510 M</b>
Code			GNVA40078
Operating pressure	bar/Mpa		75/7,5
Flow rate	l/h		600
Outlet water temperature max	°C		~100 (constant temperature)
Power supply	Ph-V-Hz/A		1-230-50
Absorbed power	kW		1,9
Motor power	kW		4-1400
Remote control			DTS
Pump(type)			IPC plunger/brass/ceramic
Boiler thermal power	kW		75
Fuel consumption	Kg/h		6,3
Fuel tank	l		18
Antiscale tank	l		2
Dimension (LxWxH)	cm		83x109x100
Weight	Kg		142

## STANDARD EQUIPMENT

CODE: IPPR40025  
HANDGRIP G6000



CODE: LCPR89117  
70 cm DOUBLE STAINLESS  
STEEL LANCE



CODE: TBAP40229  
H.P. HOSE 10 m 1/4"



CODE: LCLC40025  
70 cm LANCE WITH SPRAY  
BAR (SPRAY BAR L= 50 cm)



## OPTIONAL

CODE: PRCH40040  
ANTI-SCALE TREATMENT  
M421 10 Kg

