



IPC

BY TENNANT COMPANY

PURE WATER CLEANING SYSTEM

HPB HIGH PURE

PRESSURE

~5 bar

FLOW RATE

~5 l/min



BATTERY NOT INCLUDED

EXCLUSIVE CHARACTERISTICS

- ▶ POWER FILTER
- ▶ ERGONOMICS
- ▶ DURABILITY
- ▶ POWER PUMP
- ▶ MANOMETER

TECHNICAL DATA

Code

HPB
APTA40016

PERFORMANCE

Operating pressure	bar	~5
Pure water flow	l/min	~5
Water in/out connections	gas	3/4"
Maximum working height	m	16 (also with 2 poles)
Productivity	m ² /h	up to 200
Power supply		Gel battery (optional)
Dimension (LxWxH)	cm	53x50x127
Weight	kg	53,6

MOST FREQUENTLY USE

CONSTRUCTION INDUSTRY



GREEN ENERGIES



NAUTICAL/AUTO/TRANSPORTS



GREENHOUSES/GLASSHOUSES/
TENSILE STRUCTURES



STANDARD EQUIPMENT

CODE: FTAC40002
REVERSE OSMOSIS
MEMBRANE



CODE: PRCH40034
POWDER FOR
OSMOTIC MEMBRANE
FILTER MAINTENANCE



CODE: KTRI40106
FILTER KIT: - 1 pcs
sediment filter - 1 pcs
active carbon filter - 1 pcs
deionizing resin cartridge



CODE: TBFX40010
DRAINAGE TUBE



CODE: TBFX40009
30 m FLEXIBLE HOSE
WITH FITTINGS



CODE: VVSF40018
FLOW REGULATION
VALVE



CODE: AZMC40006
HAND-HELD TDS
METER



CODE: CNPR40007
GASKET LUBRICANT

