



HIGH-PRESSURE WASHERS - HOT WATER STATIONARY

# IWD-H

**PRESSURE**

100÷200  
bar

**FLOW RATE**

720÷1260  
l/h

**ABSORBED POWER**

3,2÷9,5  
kW

**EXCLUSIVE CHARACTERISTICS**

- ▶ DELAYED TOTAL STOP - DTS
- ▶ MICRO LEAKAGE CONTROL - MLC
- ▶ DRY RUNNING PROTECTION - DRP
- ▶ NOZZLE CLOGGING CONTROL - NCC
- ▶ INFRARED FLAME CONTROL SYSTEM - FCS
- ▶ BOILER IGNITION DELAY - IBD
- ▶ FUEL LEVEL CONTROL - FLC (OPTIONAL)
- ▶ ANTI-SCALE LEVEL CONTROL - ALC (OPTIONAL)
- ▶ LIMESCALE/CORROSION PROTECT UNIT - LCPU
- ▶ INTELLIGENT AUTOMATIC SWITCH OFF - IASF



**MOST FREQUENTLY USE**



**INNOVATIONS**



**SPECS**



STAINLESS STEEL STRUCTURE



PILOT LIGHTS INDICATING MACHINE AND BURNER FUNCTIONING, PLUS FLAME CONTROL



PROFESSIONAL PRESSURE GAUGE ENSURING A CONSTANT CONTROL OF WORKING PRESSURE

## TECHNICAL DATA

		<b>MUR. IWD-H D1012PI M</b>	<b>MUR. IWD-H D1615PI T</b>	<b>MUR. IWD-H D1618PI T</b>	<b>MUR. IWD-H D2015PI T</b>	<b>MUR. IWD-H D1521PI T</b>	<b>MUR. IWD-H D2021PI T</b>
Code		IDAC48036	IDAC48037	IDAC48038	IDAC48039	IDAC48040	IDAC48041
<b>PERFORMANCE</b>							
Operating pressure	bar/Mpa	100/10	160/16	165/16,5	200/20	150/15	200/20
Flow rate	l/h	720	900	1080	900	1260	1260
Outlet water max. temperature	°C	30-120	30-120	30-120	30-120	30-120	30-145
Power supply	Ph-V-Hz/A	1-230-50/14	3-400-50/10,5	3-400-50/13	3-400-50/14	3-400-50/13	3-400-50/16
Absorbed power	kW	3,2	6,5	7,2	7,2	7,2	9,5
Motor pole/rpm		4-1400	4-1400	4-1400	4-1400	4-1400	4-1400
Boiler thermal power	kW	67	67	88	88	88	88
Fuel consumption	l/h	5,8	5,8	7,4	7,4	7,4	7,4
Remote control		DTS	DTS	DTS	DTS	DTS	DTS
Fuel tank	l	optional (25 l)	optional (25 l)	optional (25 l)	optional (25 l)	optional (25 l)	optional (25 l)
Detergent tank	l	optional (2x25 l)	optional (2x25 l)	optional (2x25 l)	optional (2x25 l)	optional (2x25 l)	optional (2x25 l)
Detergent delivery		high pressure	high pressure	high pressure	high pressure	high pressure	high pressure
Anti-scale tank	l	2	2	2	2	2	2
Pump/head/pistons		ipg plunger/brass/ ceramic	ipg plunger/brass/ ceramic	ipg plunger/brass/ ceramic	ipg plunger/brass/ ceramic	ipg plunger/brass/ ceramic	ipg plunger/brass/ ceramic
Dimension (LxWxH)	cm	122x60x75	122x60x75	122x60x75	122x60x75	122x60x75	122x60x75
Weight	kg	170	185	190	186	186	210

## STANDARD EQUIPMENT

CODE: IPPR40025  
HANDGRIP G6000



CODE: LCPR40087  
EXTENSION P70 INOX  
(FOR 1012/1615/2015)



CODE: LCPR40159  
EXTENSION P70 INOX 0°  
(FOR 1618/1521/2021)



CODE: UGLN49993  
H.P. NOZZLE 1/4 25055  
(FOR 1012/1615)



CODE: UGLN49995  
H.P. NOZZLE 1/4 25065  
(FOR 1618/2021)



CODE: UGLN49987  
H.P. NOZZLE 1/4 15045  
(FOR 2015)



CODE: UGLN49997  
H.P. NOZZLE 1/4 15075  
(FOR 1521)



CODE: TBAP40008  
H.P.HOSER 10m 5/16"  
(FOR 1012/1615/1618/1521)



CODE: TBAP40009  
H.P.HOSE R2 10m 5/16"  
(FOR 2015)



CODE: TBAP40010  
H.P.HOSE R2 10m 3/8"  
(FOR 2021)



## OPTIONAL ACCESSORIES

CODE: AVTB39119  
INOX HOSE REEL KIT



CODE: KTRI28914  
ROTATING ARM



CODE: LCLC41140  
LANCE FOR WASHING  
FLOOR - INOX



CODE: LCPR29360  
MUDGUARD LANCE



CODE: KTRI48114  
REMOTE CONTROL WITH  
DETERGENT + WAX CONTROL



CODE: KTRI48110  
WALL FIXING BRACKET



CODE: KTRI48111  
STAND



CODE: LCPR41973  
TURBO LANCE Ø0,55 -  
(FOR 1012/1615)



CODE: LCPR88522  
TURBO LANCE Ø0,65 -  
(FOR 1618/2021)



CODE: LCPR40088  
TURBO LANCE Ø0,80 -  
(FOR 2015/1521)



CODE: LAFN48112  
FLUE EXTENSION



CODE: LCPR13557  
SANDBLASTER KIT Ø 1,6 mm  
(FOR 1012/1615)



CODE: LCPR14860  
SANDBLASTER KIT Ø 1,7 mm  
(FOR 1618/2021)



CODE: LCPR14859  
SANDBLASTER KIT Ø 1,5 mm  
(FOR 2015)



CODE: PRCH40041  
SAND BAG 25 Kg



CODE: MPVR13701  
25 l FUEL TANK 1 PCS



CODE: MPVR13701  
25 l DETERGENT TANK  
2 PCS

