



IPC

BY TENNANT COMPANY

STEAM GENERATORS

SG-20/SG-30 (STEAM+SUCTION)

PRESSURE

5÷5,5
bar

STEAM FLOW RATE

80÷100
g/min

ABSORBED POWER

3
kW



SG-20

SG-30 - BOILER WITH AUTO-FILLING TANK

EXCLUSIVE CHARACTERISTICS

- ▶ POWER BOILER
- ▶ ANTI-BUG
- ▶ SUCTION POWER
- ▶ SAFETY
- ▶ ERGONOMICS
- ▶ FLEX POWER
- ▶ DURABILITY

MOST FREQUENTLY USE

AUTOMOTIVE



HO.RE.CA.



FOOD INDUSTRY AND RETAILERS




LARGE COMMON AREAS



SPECS



HANDLE FOR A CONVENIENT TRANSPORTATION.



CONTROL PANEL ENSURING A CONSTANT CHECK OF MACHINE MAIN FUNCTIONS.



ROTARY KNOB FOR STEAM QUANTITY CONTROLLER

TECHNICAL DATA

		SG-20 S 5008 M	SG-30 P 5510 M
Code		GNVA40016	GNVA40017
PERFORMANCE			
Operating pressure	bar/Mpa	5/0,5	5,5/0,55
Steam flow rate	g/min	0-80	0-100
Max steam temperature	°C	140	140
Start up time	min	~ 7	~ 7
Power supply	Ph-V-Hz	1-230-50	1-230-50
Max absorbed power	kW	3	3
Boiler volume	l	2,2	2,2 (auto-filling)
Water/detergent tank	l	2	2
Dimension (LxWxH)	cm	57x40x65	57x40x65
Weight	kg	16	16,6

STANDARD EQUIPMENT

CODE: IPIP45757
HANDGRIP + HOSE
STEAM/SUCTION 2,5 m
(FOR SG-20)



CODE: IPIP40001
HANDGRIP + HOSE
STEAM/SUCTION 2,5 m
(FOR SG-30)



CODE: KTRI46482
ACCESSORIES KIT
STEAM/SUCTION



OPTIONAL ACCESSORIES

CODE: IPIP47898
HANDGRIP + HOSE
STEAM 2,5 m
(FOR SG-20)



CODE: IPIP45815
HANDGRIP + HOSE
STEAM 5 m
(FOR SG-30)



CODE: KTRI40275
STEAM ONLY
ACCESSORIES KIT



CODE: KTRI89496
TROLLEY



CODE: KTRI40269
DESCALING KIT (5 BAGS)



CODE: SPPV46076
BRASS BRUSH Ø30



CODE: SPPV40035
BRASS BRUSH Ø50

