



IPC

BY TENNANT COMPANY

STEAM GENERATORS

SG-45 (ONLY STEAM)

SOFT TOUCH PANEL

PRESSURE

5
bar

STEAM FLOW RATE

100
g/min

ABSORBED POWER

2,9
kW



EXCLUSIVE CHARACTERISTICS

- ▶ POWER BOILER
- ▶ ANTI-BUG
- ▶ POWER FILTER
- ▶ AUTOMATIC SHUTDOWN
- ▶ SAFETY
- ▶ ERGONOMICS
- ▶ FLEX POWER
- ▶ DURABILITY

MOST FREQUENTLY USE

AUTOMOTIVE



HO.RE.CA.



FOOD INDUSTRY AND RETAILERS



LARGE COMMON AREAS




SPECS



STEAM HOSE HOOK
EQUIPPED WITH SAFETY
PANEL



ROTARY KNOB FOR STEAM
FLOW RATE CONTROLLER



NON-MARKING WHEELS

TECHNICAL DATA

		SG-45 5008 M
Code		GNVA40020
PERFORMANCE		
Operating pressure	bar/Mpa	2,5-5/0,25-0,5
Steam flow rate	g/min	0-100
Max steam temperature	°C	160
Start up time	min	~ 6
Power supply	Ph-V-Hz/A	1-230-50/13
Max absorbed power	kW	2,85
Boiler volume	l	3
Water tank	l	7
Detergent tank	l	2
Dimension (LxWxH)	cm	66x43x67
Weight	Kg	20,2

STANDARD EQUIPMENT

CODE: IPIP45815
HANDGRIP + HOSE
STEAM 5 m



CODE: KTRI40275
STEAM ONLY
ACCESSORIES KIT



CODE: MPVR88900
TANK 5 l



OPTIONAL ACCESSORIES

CODE: IPIP40003
HANDGRIP + HOSE
STEAM 8 m



CODE: KTRI89495
TROLLEY



CODE: KTRI40269
DESCALING KIT (5 BAGS)

