



HIGH-PRESSURE WASHERS - HOT STATIONARY

IWD-H

PRESSURE

100÷200
bar

FLOW RATE

720÷1260
l/h

ABSORBED POWER

3,2÷9,5
kW

EXCLUSIVE CHARACTERISTICS

- ▶ DELAYED TOTAL STOP - DTS
- ▶ MICRO LEAKAGE CONTROL - MLC
- ▶ DRY RUNNING PROTECTION - DRP
- ▶ NOZZLE CLOGGING CONTROL - NCC
- ▶ INFRARED FLAME CONTROL SYSTEM - FCS
- ▶ BOILER IGNITION DELAY - IBD
- ▶ FUEL LEVEL CONTROL - FLC
- ▶ ANTI-SCALE LEVEL CONTROL - ALC
- ▶ LIMESCALE/CORROSION PROTECT UNIT - LCPU
- ▶ INTELLIGENT AUTOMATIC SWITCH OFF - IASF



MOST FREQUENTLY USE

AUTOMOTIVE



AGRICULTURE



CONSTRUCTION INDUSTRY



MUNICIPALITIES



DIY AND GARDENING



HEAVY INDUSTRY



INNOVATIONS



G6000™
CERAMIC
TECH GUN

SPECS



STAINLESS STEEL
STRUCTURE



PILOT LIGHTS INDICATING
MACHINE AND BURNER
FUNCTIONING, PLUS FLAME
CONTROL



PROFESSIONAL PRESSURE
GAUGE ENSURING A
CONSTANT CONTROL OF
WORKING PRESSURE

TECHNICAL DATA

		MUR. IWD-H D1012PI M	MUR. IWD-H D1615PI T	MUR. IWD-H D1618PI T	MUR. IWD-H D2015PI T	MUR. IWD-H D1521PI T	MUR. IWD-H D2021PI T
Code		IDAC48036	IDAC48037	IDAC48038	IDAC48039	IDAC48040	IDAC48041
PERFORMANCE							
Operating pressure	bar/Mpa	100/10	160/16	165/16,5	200/20	150/15	200/20
Flow rate	l/h	720	900	1080	900	1260	1260
Outlet water max. temperature	°C	30-120	30-120	30-120	30-120	30-120	30-145
Power supply	Ph-V-Hz/A	1-230-50/14	3-400-50/10,5	3-400-50/7,2	3-400-50/14	3-400-50/13	3-400-50/16
Absorbed power	kW	3,2	6,5	7,2	7,2	7,2	9,5
Motor pole/rpm		4-1400	4-1400	4-1400	4-1400	4-1400	4-1400
Boiler thermal power	kW	67	67	88	88	88	88
Fuel consumption	l/h	5,8	5,8	7,4	7,4	7,4	7,4
Remote control		DTS	DTS	DTS	DTS	DTS	DTS
Fuel tank	l	optional (25 l)	optional (25 l)	optional (25 l)	optional (25 l)	optional (25 l)	optional (25 l)
Detergent tank	l	optional (2x25 l)	optional (2x25 l)	optional (2x25 l)	optional (2x25 l)	optional (2x25 l)	optional (2x25 l)
Detergent delivery		high pressure	high pressure	high pressure	high pressure	high pressure	high pressure
Pump/head/pistons		lpg plunger/brass/ceramic	lpg plunger/brass/ceramic	lpg plunger/brass/ceramic	lpg plunger/brass/ceramic	lpg plunger/brass/ceramic	lpg plunger/brass/ceramic
Dimension (LxWxH)	cm	122x60x75	122x60x75	122x60x75	122x60x75	122x60x75	122x60x75
Weight	kg	170	180	180	180	205	205

STANDARD EQUIPMENT

CODE: IPPR40020
HANDGRIP G6000



CODE: LCPR40087
EXTENSION P70 INOX
(FOR 1012/1615/2015)



CODE: LCPR40159
EXTENSION P70 INOX 0°
(FOR 1618/1521/2021)



CODE: UGLN49993
H.P. NOZZLE 1/4 UG.25055
(FOR 1012/1615)



CODE: UGLN49995
H.P. NOZZLE 1/4 UG.25065
(FOR 1618/2021)



CODE: UGLN49987
H.P. NOZZLE 1/4
UG.15045 (FOR 2015)



CODE: UGLN49997
H.P. NOZZLE 1/4
UG.15075 (FOR 1521)



CODE: TBAP40008
H.P.HOSER 10 m 5/16" M22
(FOR 1012/1615/1618/1521)



CODE: TBAP40009
H.P.HOSE R2 10 m 5/16"
M22 (FOR 2015)



CODE: TBAP40010
H.P.HOSE R2 10 m 3/8"
M22 (FOR 2021)



OPTIONAL ACCESSORIES

CODE: AVTB39119
INOX HOSE REEL KIT



CODE: KTRI28914
ROTATING ARM



CODE: LCLC41140
LANCE FOR WASHING
FLOOR - INOX



CODE: LCPR29360
MUDGUARD LANCE



CODE: KTRI48114
REMOTE CONTROL WITH
DETERGENT + WAX CONTROL



CODE: KTRI48110
WALL FIXING BRACKET



CODE: KTRI48111
STAND



CODE: LCPR13557
SANDBLASTER KIT Ø 1,6 mm
(FOR 1012/1615)



CODE: LCPR14860
SANDBLASTER KIT Ø 1,7 mm
(FOR 1618/2021)



CODE: LCPR14859
SANDBLASTER KIT Ø 1,5 mm
(FOR 2015)



CODE: LCPR14861
SANDBLASTER KIT Ø 2 mm
(FOR 1521)




CODE: PRCH00065
SAND BAG 50 Kg



CODE: KTRI87713
KIT FOR HOT WATER FEEDING
VERSION (FOR 1012)



CODE: KTRI49930
KIT FOR HOT WATER FEEDING
VERSION
(FOR 1615/2015/1521/2021)



CODE: KTRI49931
KIT FOR HOT WATER FEEDING
VERSION (FOR 1618)

