



CONDUCTIVE & STATIC DISSIPATIVE PLASTIC



CONDUCTIVE & STATIC DISSIPATIVE PLASTIC

PLANET 152 ATEX CE EX II 3D Ex t IIIB T135°C Dc IP55

PLANET 202 ATEX CE EX II 3D Ex t IIIB T135°C Dc IP55

EXCLUSIVE FEATURES

- ▶ RELIABLE CONSTRUCTION FOR INTENSIVE USE
- ▶ DETACHABLE TANK AND SOLID CART
- ▶ MANUAL FILTER SHAKER
- ▶ BIG AND BRAKED WHEELS
- ▶ INDUSTRIAL FRAMEWORK WITH AISI 304 WITH DETACHABLE TANK
- ▶ STARSHAPED FILTER, PCB PREFILTER AND ADDITIONAL CARTRIDGE
- ▶ VACUUM RELIEF VALVE AND FILTRATION LEVEL INDICATOR
- ▶ LONG LASTING TURBINE WITH PERFECT PERFORMANCE
- ▶ EXPLOSION PROOF TURBINE AND DESIGN FOR ATEX ZONE 22
- ▶ CONDUCTIVE WHEELS WITH BRAKES
- ▶ STATIC DISSIPATING FILTERS
- ▶ PCB PREFILTER & ADDITIONAL CARTRIDGE

EXCLUSIVE FEATURES

- ▶ RELIABLE CONSTRUCTION FOR INTENSIVE USE
- ▶ DETACHABLE TANK AND SOLID CART
- ▶ MANUAL FILTER SHAKER
- ▶ DOUBLE STAGE MOTORS AND TURBINE
- ▶ BIG AND BRAKED WHEELS
- ▶ INDUSTRIAL FRAMEWORK WITH AISI 304 WITH DETACHABLE TANK
- ▶ STARSHAPED FILTER, PCB PREFILTER AND ADDITIONAL CARTRIDGE
- ▶ VACUUM RELIEF VALVE AND FILTRATION LEVEL INDICATOR
- ▶ LONG LASTING TURBINE WITH PERFECT PERFORMANCE
- ▶ EXPLOSION PROOF TURBINE AND DESIGN FOR ATEX ZONE 22
- ▶ CONDUCTIVE WHEELS WITH BRAKES
- ▶ STATIC DISSIPATING FILTERS
- ▶ PCB PREFILTER & ADDITIONAL CARTRIDGE

| | | PLANET 152 ATEX |
|----------------------|--------------------|-----------------|
| Code | | ASID00379 |
| TECHNICAL DATA | | |
| Usage | | DRY |
| Number of phases | | 1 |
| Voltage | V | 220-240 |
| Turbine | | 1xsingle stage |
| Power | W | 1500 |
| Water lift | mmH ₂ O | 1800 |
| Airflow | m ³ /h | 220 |
| Tank Capacity | l | 35 |
| Diameter of inlet | mm | 60 |
| Filtering surface | cm ² | 12.000 |
| Sound Pressure Level | dB(A) | 74 |
| Dimensions (LxWxH) | mm | 710x660x1280 |
| Weight | Kg | 62.5 |

| | | PLANET 202 ATEX |
|----------------------|--------------------|-----------------|
| Code | | ASID00412 |
| TECHNICAL DATA | | |
| Usage | | DRY |
| Number of phases | | three phase |
| Voltage | V | 400 |
| Turbine | | 1xsingle stage |
| Power | W | 3000 |
| Water lift | mmH ₂ O | 2500 |
| Airflow | m ³ /h | 304 |
| Tank Capacity | l | 40 |
| Diameter of inlet | mm | 60 |
| Filtering surface | cm ² | 19.500 |
| Sound Pressure Level | dB(A) | 76 |
| Dimensions (LxWxH) | mm | 680x700x1360 |
| Weight | Kg | 60 |

STANDARD EQUIPMENT

CODE: KTRI03141 CONDUCTIVE FILTERING KIT
 CODE: FTDP00223 POLYCARBON PREFILTER



STANDARD EQUIPMENT

CODE: KTRI04594 CONDUCTIVE FILTERING KIT
 CODE: FTDP40014 POLYCARBON PREFILTER



OPTIONAL ACCESSORIES

| | |
|---------------------------------|-----------|
| Anti-Static tool kit Ø50-60 mm | PMDT00436 |
| Anti-Static tool kit Ø38-60 mm | PMDT00326 |
| High Reach Cleaning ATEX | AVAILABLE |
| Hepa cartridge kit | KTRI03681 |
| Nylon filter for exhausting air | FTDP00410 |
| Connection for nylon filter | RCVR00878 |

OPTIONAL ACCESSORIES

| | |
|--------------------------------|-----------|
| Anti-Static tool kit Ø50-60 mm | PMDT00436 |
| Anti-Static tool kit Ø38-60 mm | PMDT00326 |
| High Reach Cleaning ATEX | AVAILABLE |