



PNEUMATIC/
AIR OPERATED



PLANET 300S PN ATEX CE EX II 3D Ex t IIIB T135°C Dc IP55

CARATTERISTICHE ESCLUSIVE

- ▶ RELIABLE CONSTRUCTION FOR INTENSIVE USE
- ▶ DETACHABLE TANK AND SOLID CART
- ▶ MANUAL FILTER SHAKER
- ▶ TANGENTIAL OR METAL INLET
- ▶ FILTER OVERPRESSURE INDICATORS
- ▶ EXPLOSION PROOF TURBINE AND DESIGN FOR ATEX ZONE 22
- ▶ STATIC DISSIPATING FILTERS
- ▶ PCB PREFILTER AND ADDITIONAL CARTRIDGE
- ▶ GROUNDING SYSTEM

PLANET 300 S PN ATEX ASID00293

Codice

TECHNICAL DATA

Usage		DRY
Air consumption	l/min	700-1300
Air pressure	bar	6
Water lift	mmH ₂ O	2200-3300
Air flow	m ³ /h	330
Tank capacity	l	100
Diameter of inlet	mm	70
Dimensions (LxWxH)	mm	630 x 890 x 1650
Weight	kg	72

ACCESSORI STANDARD

CODICE: KTRI04594
CONDUCTIVE
FILTERING KIT



CODICE: FTDP40014
POLYCARBON PREFILTER



CODICE: FTDP00375
POLY CARTRIDGE 10.000
cm²



ACCESSORI OPZIONALI

Anti-static kit tools for inlet Ø50-70 mm	PMDT00426
Stainless steel float kit to recovery liquid (for Planet 100 lt)	KTRI03124
Reusable conductive bag Atex (for Planet 100 lt)	KTRI03175
Retainer plate with clip (for conductive bag)	PVWR00190