



STEAM GENERATORS

SG-50 M

PRESSURE

5
bar

STEAM FLOW RATE

80÷100
g/min

ABSORBED POWER

2,9÷3,5
kW

EXCLUSIVE CHARACTERISTICS

- ▶ POWER BOILER
- ▶ ANTI-BUG
- ▶ POWER FILTER
- ▶ AUTOMATIC SHUTDOWN
- ▶ SAFETY
- ▶ ERGONOMICS
- ▶ FLEX POWER
- ▶ DURABILITY

MOST FREQUENTLY USE

AUTOMOTIVE



HO.RE.CA.



FOOD INDUSTRY AND RETAILERS



LARGE COMMON AREAS



INNOVATIONS



SPECS



STAINLESS STEEL STRUCTURE, SUITABLE FOR AREAS WHERE HYGIENE IS A MUST



CONTROL PANEL WITH MICRO-TOUCH BUTTONS FOR A QUICK AND CONSTANT CHECK OF MACHINE MAIN FUNCTIONS.



ROTARY KNOB FOR STEAM QUANTITY CONTROL



- 1 Fixed 'Steam-only' station module
- 2 Module available with vacuum cleaner included for combo 'steam+suction' applications 
- 3 'Steam-only' module can be placed on trolley to facilitate manoeuvrability and transport 
- 4 'steam+suction' module can also be placed on trolley to facilitate manoeuvrability and transport 

TECHNICAL DATA

		SG-50 S 5008 M	SG-50 S 5010 M
Code		GNVA40024	GNVA40025
PERFORMANCE			
Operating pressure	bar/Mpa	2,5-5/0,25-0,5	2,5-5/0,25-0,5
Steam flow rate	g/min	80	0-100
Max steam temperature	°C	150	160
Start up time	min	~ 5	~ 5
Power supply	Ph-V-Hz	1-230-50	1-230-50
Max absorbed power	kW	2,9	3,5
Boiler volume	l	4	4
Water tank	l	6	6
Dimension (LxWxH)	cm	57x40x80	57x40x80
Weight	kg	30	30

STANDARD EQUIPMENT

CODE: MPVR88900
TANK 5 l



OPTIONAL ACCESSORIES

CODE: IPIP40004
HANDGRIP + HOSE
STEAM/SUCTION MT 5 m



CODE: KTRI40277
ACCESSORIES KIT
STEAM/SUCTION



CODE: KTRI40272
WET & DRY VACUUM
CLEANER



CODE: IPIP45815
HANDGRIP + HOSE
ONLY STEAM 5 m



CODE: KTRI40275
STEAM ACCESSORIES KIT



CODE: KTRI40269
DESCALING KIT
(10 PHIALS)



CODE: KTRI40271
TROLLEY

