



STEAM GENERATORS

# SG-50 T (THREE-PHASE)

PRESSURE

7 bar

FLOW RATE

100 g/min

ABSORBED POWER

7,5 kW

## EXCLUSIVE CHARACTERISTICS

- ▶ POWER BOILER
- ▶ ANTI-BUG
- ▶ POWER FILTER
- ▶ AUTOMATIC SHUTDOWN
- ▶ SAFETY
- ▶ ERGONOMICS
- ▶ FLEX POWER
- ▶ DURABILITY

## MOST FREQUENTLY USE

AUTOMOTIVE

HO.RE.CA.

FOOD INDUSTRY AND RETAILERS

LARGE COMMON AREAS

## INNOVATIONS



## SPECS



STAINLESS STEEL STRUCTURE, SUITABLE FOR AREAS WHERE HYGIENE IS A MUST



CONTROL PANEL WITH MICRO-TOUCH BUTTONS FOR A QUICK AND CONSTANT CHECK OF MACHINE MAIN FUNCTIONS



STEAM HOSE HOOK IS PLACED ON TOP OF THE MACHINE FOR A COMFORTABLE USE



1 Fixed 'steam-only' station module

2 Module available with vacuum cleaner included, for combo 'steam+suction' applications



3 'steam-only' module can be placed on trolley to facilitate manoeuvrability and transport.



4 'steam+suction' module can also be placed on trolley to facilitate manoeuvrability and transport



## TECHNICAL DATA

		<b>SG-50 S 5014 T</b>
Code		GNVA40028
PERFORMANCE		
Operating pressure	bar/Mpa	4,5-7/0,45-0,7
Steam flow rate	g/min	100
Max steam temperature	°C	155
Start up time	min	~ 5
Power supply	Ph-V-Hz	3-400-50
Max absorbed power	kW	7,5
Boiler volume	l	4
Water tank	l	6
Dimension (LxWxH)	cm	57x40x80
Weight	kg	35

## STANDARD EQUIPMENT

CODE: MPVR88900  
TANK 5 l



## OPTIONAL ACCESSORIES

CODE: IPIP40004  
HANDGRIP + HOSE  
STEAM/SUCTION 5 m



CODE: KTRI40277  
ACCESSORIES KIT  
STEAM/SUCTION



CODE: KTRI40272  
WET & DRY VACUUM  
CLEANER



CODE: IPIP45815  
HANDGRIP + HOSE  
ONLY STEAM 5 m



CODE: KTRI40275  
STEAM ACCESSORIES KIT



CODE: KTRI40269  
DESCALING KIT  
(10 PHIALS)



CODE: KTRI40271  
TROLLEY

