



HIGH-PRESSURE WASHERS - HOT WATER

PW-H50 PLUS*

DELAYED TOTAL STOP MODELS

PRESSURE

100÷200
bar

FLOW RATE

600÷1000
l/h

ABSORBED POWER

3÷6,4
kW

EXCLUSIVE CHARACTERISTICS

- ▶ DELAYED TOTAL STOP - DTS
- ▶ INTELLIGENT AUTOMATIC SWITCH OFF - IASF
- ▶ MICRO LEAKAGE CONTROL - MLC
- ▶ DRY RUNNING PROTECTION - DRP
- ▶ NOZZLE CLOGGED CONTROL - NCC
- ▶ BOILER IGNITION DELAY - IBD
- ▶ WORKING HOURS COUNTER - WHC
- ▶ ELECTRONIC TEMPERATURE STABILIZER CONTROL - ETSC
- ▶ LIMESCALE/CORROSION PROTECTION UNIT - LCPU
- ▶ ANTI-SCALE LEVEL CONTROL - ALC
- ▶ FUEL LEVEL CONTROL - FLC
- ▶ MAINTENANCE CHECK LED - MCL



PW-H50 PLUS



PW-H50/4 PLUS

* PLUS VERSION

MOST FREQUENTLY USE

AUTOMOTIVE



AGRICULTURE



CONSTRUCTION INDUSTRY



MUNICIPALITIES



DIY AND GARDENING



HEAVY INDUSTRY



INNOVATIONS



G6000™
CERAMIC
TECH GUN



IPC
PUMP



MODULAR
BUILD-UP



MSCT™
MULTIFUNCTION
SAFETY
CONTROL



ALL
TERRAIN



IPC'S
EXCLUSIVE
BOILER



M421
ANTI-SCALE



ETC™
ELECTRONIC
TEMPERATURE
CONTROL

SPECS



CONTROL PANEL WITH
INDICATORS LAMPS



ERGONOMIC HANDLE PROVIDED
WITH LANCE HOLDER FOR AN
EASY TRANSPORT



ACCESSORIES STORAGE
COMPARTMENT

TECHNICAL DATA

		PW-H50P D1310P4 M	PW-H50P D1012P4 M	PW-H50P D1813P4 T	PW-H50P D1915P4 T	PW-H50P D2017P4 T
3 WHEELS						
Code		IDAC40873	IDAC40874	IDAC40875	IDAC40876	IDAC40877
4 WHEELS						
Code		IDAC40883	IDAC40884	IDAC40885	IDAC40886	IDAC40887
PERFORMANCE						
Operating pressure	bar/Mpa	30-130/3-13	30-100/3-10	30-180/3-18	30-190/3-19	30-200/3-20
Flow rate	l/h	300-600	360-720	450-800	450-900	500-1000
Outlet water temperature	°C	30-140	30-140	30-140	30-140	3-140
Power supply	Ph-V-Hz/A	1-230-50/13,8	1-230-50/14	3-400-50/9,7	3-400-50/10,6	3-400-50/13,2
Absorbed power	kW	3,1	3,2	5	5	6,4
Motor pole/rpm		4-1400	4-1400	4-1400	4-1400	4-1400
Remote control		DTS	DTS	DTS	DTS	DTS
Pump/head/pistons		lpc plunger/brass/ ceramic	lpc plunger/brass/ ceramic	lpc plunger/brass/ ceramic	lpc plunger/brass/ ceramic	lpc plunger/brass/ ceramic
Boiler thermal power	kW	40	55	70	70	≥70
Fuel consumption	kg/h	3,2	5,8	5,8	5,8	5,8
Fuel tank	l	25	25	25	25	25
Detergent tank	l	22	22	22	22	22
Detergent delivery		high pressure	high pressure	high pressure	high pressure	high pressure
Dimension (LxWxH)	cm	110x70x90	110x70x90	110x70x90	110x70x90	110x70x90
Weight	kg	107	109	120	122	140

STANDARD EQUIPMENT

CODE: IPPR40025
HANDGRIP G6000



CODE: LCPR40087
EXTENSION P70 - INOX



CODE: UGLN49986
H.P. NOZZLE 1/4 1504
(FOR 1310/1813)



CODE: UGLN05200
H.P. NOZZLE 1/4 1505
(FOR 1012)



CODE: UGLN49987
H.P. NOZZLE 1/4 15045
(FOR 1915/2017)



CODE: TBAP25324
HIGH PRESSURE HOSE 10 m



OPTIONAL ACCESSORIES

CODE: SPID24939
FIXED HYDROBRUSH
LANCE P70



CODE: LCLC41140
LANCE FOR WASHING
FLOORS INOX



CODE: LCLC49492
LANCE FOR WASHING FLOORS
Ø 0,35 (FOR 1310/1915)



CODE: LCLC49494
LANCE FOR WASHING
FLOORS Ø 0,55 (FOR 1012)



CODE: LCLC49493
LANCE FOR WASHING FLOORS
Ø 0,45 (FOR 1813/2017)



CODE: KTRI40235
HOSE REEL KIT



CODE: RCIN10810
HOSE COUPLING M22



CODE: TBAP23853
DRAIN KIT 10 m



CODE: LCPR40104
EXTENSIO P70 + TPR255
Ø 0,35 (FOR 1310/1813)



CODE: LCPR40135
EXTENSIO P70 + TPR255
Ø 0,45 (FOR 1012/1915/2017)



CODE: LCPR14859
SANDBLASTER KIT Ø 1,5 mm
(FOR 1915/2017)



CODE: LCPR14858
SANDBLASTER KIT Ø 1,4 mm
(FOR 1310/1813)



CODE: LCPR13557
SANDBLASTER KIT Ø 1,6 mm
(FOR 1012)



CODE: PRCH40041
SAND BAG 25 Kg



CODE: PRCH40039
ANTI-SCALE TREATMENT
M421 1 Kg X 6



CODE: PRCH40040
ANTI-SCALE TREATMENT
M421 10 Kg



CODE: KTRI40316
MAINTENANCE KIT 500H
(FOR 1310)



CODE: KTRI40314
MAINTENANCE KIT 500H
(FOR 1813/1915)



CODE: KTRI40430
MAINTENANCE KIT 500H
(FOR 1012)



CODE: KTRI40431
MAINTENANCE KIT 500H
(FOR 2017)

