



SCRUBBER DRIERS - WALK BEHIND

CT30

MAX PRODUCTIVITY

1575 m²/h

BATTERIES RUNNING TIME

2,5 h
1,5 h eco version

WATER TANK RUNNING TIME

45'
working session



BATTERIES AND BATTERY CHARGER INCLUDED

MOST FREQUENTLY USE



INNOVATIONS



ECO SELECT



DBL™ DOUBLE BATTERY LIFE



SLS™ SELF LEVELING SYSTEM



BACTERIA CONTROL

SPECS



FOLDABLE HANDLE



PRESET WORKING PROGRAMS



THREE STAGE VACUUM MOTOR

TECHNICAL DATA

		CT30 B45	CT30 C45	CT30 B45 ECO
Code		LPTB02435	LPTB00531	LPTB01523
PERFORMANCE				
Max theoretical productivity	m ² /h	1575	1575	1575
Cleaning path	mm	460	450	460
Water tank capacity (solution recovery)	l	28/30	28/30	28/30
Max running time	min	150	Unlimited	150
Voltage	V-Ah	24(2x12)-74 AGM	230-50/60	24(2x12)-50 AGM
Installed power	W	900	700	900
Brush pressure	kg	17/21	17/21	17/21
Squeegee width	mm	550	550	550
Max speed	km/h	3,5	3,5	3,5
Weight	kg	98	53	98
Dimension (LxWxH)	mm	960x550x1220	960x550x1220	960x550x1220

STANDARD ACCESSORIES

	CT30 B45	CT30 C45	CT30 B45 ECO
BRUSHES			
BRUSH	SPPV01188	SPPV01188	SPPV01188
SQUEEGEE BLADES			
LATEX FRONT BLADE	MPVR05953 - 660mm	MPVR05953 - 660mm	MPVR05953 - 660mm
LATEX REAR BLADE	MPVR05954 - 715mm	MPVR05954 - 715mm	MPVR05954 - 715mm

CONSUMABLES (Codes available on price list)

BRUSHES



PADS/SUPER PADS



SQUEEGEE BLADES



OPTIONAL ACCESSORIES

CODE: MPVR05966
SPLASH GUARD



CODE: KTRI02257
EXTERNAL SUCTION KIT



CODE: KTRI02084
REAR HD SQUEEGEE KIT



CODE: PRCH00578
BIOSAN RAPIDE WT
(30PCS/30DAYS)



BATTERIES AND BATTERY CHARGERS

BATTERIES	N°	CHARACTERISTICS	DIMENSION	RUNNING TIME	BATTERY CHARGERS
IPC AGM battery BAAC00117	2	12V 74 Ah (C5)	257x172x212	150 min	On board battery charger 24V 10Ah KTRI02245
EXIDE gel battery BAAC00124	2	12V 63 Ah (C5)	261x171x210	130 min	On board battery charger 24V 10Ah KTRI02245
AGM battery (only Eco) BAAC00134	2	12V 50 Ah (C5)	229x138x212	90 min	On board battery charger 24V 5 Ah KTRI02244

RECOMMENDED BATTERIES AND BATTERY CHARGER