



STEAM GENERATORS

# SG-20/SG-30 (STEAM+SUCTION)

PRESSURE

5÷5,5  
bar

STEAM FLOW RATE

80÷100  
g/min

ABSORBED POWER

3  
kW



SG-20

SG-30 - BOILER WITH AUTO-FILLING TANK

## EXCLUSIVE CHARACTERISTICS

- ▶ POWER BOILER
- ▶ ANTI-BUG
- ▶ SUCTION POWER
- ▶ SAFETY
- ▶ ERGONOMICS
- ▶ FLEX POWER
- ▶ DURABILITY

## MOST FREQUENTLY USE

AUTOMOTIVE



HO.RE.CA.



FOOD INDUSTRY AND RETAILERS




LARGE COMMON AREAS



## SPECS



HANDLE FOR A CONVENIENT TRANSPORTATION.



CONTROL PANEL ENSURING A CONSTANT CHECK OF MACHINE MAIN FUNCTIONS.



ROTARY KNOB FOR STEAM QUANTITY CONTROLLER

## TECHNICAL DATA

		<b>SG-20 S 5008 M</b>	<b>SG-30 P 5510 M</b>
Code		GNVA40016	GNVA40017
<b>PERFORMANCE</b>			
Operating pressure	bar/Mpa	5/0,5	5,5/0,55
Steam flow rate	g/min	0-80	0-100
Max steam temperature	°C	140	140
Start up time	min	~ 7	~ 7
Power supply	Ph-V-Hz	1-230-50	1-230-50
Max absorbed power	kW	3	3
Boiler volume	l	2,2	2,2 (auto-filling)
Water/detergent tank	l	2	2
Dimension (LxWxH)	cm	57x40x65	57x40x65
Weight	kg	16	18

## STANDARD EQUIPMENT

CODE: IPIP45757  
**HANDGRIP + HOSE  
 STEAM/SUCTION 2,5 m  
 (FOR SG-20)**



CODE: IPIP40001  
**HANDGRIP + HOSE  
 STEAM/SUCTION 2,5 m  
 (FOR SG-30)**



CODE: KTRI46482  
**ACCESSORIES KIT  
 STEAM/SUCTION**



## OPTIONAL ACCESSORIES

CODE: IPIP47898  
**HANDGRIP + HOSE  
 STEAM 2,5 m  
 (FOR SG-20)**



CODE: IPIP45815  
**HANDGRIP + HOSE  
 STEAM 5 m  
 (FOR SG-30)**



CODE: KTRI40275  
**STEAM ONLY  
 ACCESSORIES KIT**



CODE: KTRI89496  
**TROLLEY**



CODE: KTRI40269  
**DESCALING KIT  
 (10 PHIALS)**



CODE: SPPV46076  
**BRASS BRUSH Ø30**



CODE: SPPV40035  
**BRASS BRUSH Ø50**

