



STEAM GENERATORS

# SG-50 T

THREE-PHASE (ONLY STEAM - OPTIONAL VACUUM)

PRESSURE

7 bar

FLOW RATE

140 g/min

ABSORBED POWER

7,5 kW

### EXCLUSIVE CHARACTERISTICS

- ▶ POWER BOILER
- ▶ ANTI-BUG
- ▶ POWER FILTER
- ▶ AUTOMATIC SHUTDOWN
- ▶ SAFETY
- ▶ ERGONOMICS
- ▶ FLEX POWER
- ▶ DURABILITY

### MOST FREQUENTLY USE

AUTOMOTIVE

HO.RE.CA.

FOOD INDUSTRY AND RETAILERS

LARGE COMMON AREAS

### INNOVATIONS



### SPECS



STAINLESS STEEL STRUCTURE, SUITABLE FOR AREAS WHERE HYGIENE IS A MUST






CONTROL PANEL WITH MICRO-TOUCH BUTTONS FOR A QUICK AND CONSTANT CHECK OF MACHINE MAIN FUNCTIONS



STEAM HOSE HOOK IS PLACED ON TOP OF THE MACHINE FOR A COMFORTABLE USE



- 1 Fixed 'steam-only' station module
- 2 Module available with vacuum cleaner included, for combo 'steam+suction' applications 
- 3 'steam-only' module can be placed on trolley to facilitate manoeuvrability and transport. 
- 4 'steam+suction' module can also be placed on trolley to facilitate manoeuvrability and transport. 

## TECHNICAL DATA

<b>Code</b>		<b>SG-50 S 5014 T</b>
		GNVA40028
<b>PERFORMANCE</b>		
<b>Operating pressure</b>	bar/Mpa	4,5-7/0,45-0,7
<b>Steam flow rate</b>	g/min	0-140
<b>Max steam temperature</b>	°C	160
<b>Start up time</b>	min	~ 5
<b>Power supply</b>	Ph-V-Hz/A	3-400-50/10,7
<b>Max absorbed power</b>	kW	7,1
<b>Boiler volume</b>	l	4
<b>Water tank</b>	l	6
<b>Detergent tank</b>	l	6
<b>Dimension (LxWxH)</b>	cm	57x40x80
<b>Weight</b>	Kg	35

## STANDARD EQUIPMENT

CODE: MPVR88900  
TANK 5 l



## OPTIONAL ACCESSORIES

CODE: IPIP40004  
HANDGRIP + HOSE  
STEAM/SUCTION 5 m



CODE: KTRI40277  
ACCESSORIES KIT  
STEAM/SUCTION



CODE: KTRI40272  
WET & DRY VACUUM  
CLEANER



CODE: IPIP45815  
HANDGRIP + HOSE  
ONLY STEAM 5 m



CODE: KTRI40275  
STEAM ACCESSORIES KIT



CODE: KTRI40269  
DESCALING KIT  
(10 PHIALS)



CODE: KTRI40271  
TROLLEY

