



IPC

BY TENNANT COMPANY

VACUUM CLEANERS - SPECIAL SOLUTIONS - FLOODED AREA EMPTYING

GC 2/107 SUB+

POWER MAX

2400
W

WATER LIFT

2470
mmH₂O

AIRFLOW

420
m³/h

TANK CAPACITY

107
l



PUMP
OUT

EXCLUSIVE FEATURES

- ▶ AP TUBE
- ▶ INNOVATIVE GASKET
- ▶ STRONG HOOKS
- ▶ INDEPENDENT MOTORS WITH LIGHT SWITCHES
- ▶ SEALANT FLOATER & INTEGRATED ANTIFOAM SYSTEM
- ▶ TIPPING TROLLEY
- ▶ RELIABLE CONSTRUCTION FOR INTENSIVE USE
- ▶ SUBMERSIBLE PUMP
- ▶ DOUBLE STAGE MOTORS

MOST FREQUENTLY USE

AGRICULTURE



CONSTRUCTION



HARDWARE CUSTOMER



HEAVY INDUSTRY



AUTOMOTIVE



INNOVATIONS



BLACK IS GREEN™



NEW BLEND FLEXIBLE HOSE

SPECS



HIGH EFFICIENCY STAINLESS STEEL SUBMERSIBLE PUMP FOR INDUSTRIAL APPLICATION



WATER FLOW VALVE



TIPPING TROLLEY

TECHNICAL DATA

Code		GC 2/107 SUB+
PERFORMANCE		ASD015530
Usage		WET
Motor		2x2 stage
Power	W	2400 max
Voltage	V	220-240
Water lift	mmH ₂ O	2470
Airflow	m ³ /h	420
Tank Capacity/Material	l	107/plastic (polyethylene)
Cable length	m	8,5
Sound Pressure Level (EN 60704-1; EN 60704-2-1; IEC 60335-2-69)	dB(A)	77
Pump type		Stainless Steel
Pump power	W	750
Pump capacity	l/min	400
Solids diameter for pumping out	mm	40 max
Delivery head	m	11,5
Diameter of accessories	mm	38
Dimensions (LxWxH)	mm	500x620x1110
Weight	kg	32,0

STANDARD EQUIPMENT

CODE: TBFX01277
**EXTRA STRONG FLEXIBLE
HOSE 5 m Ø38 mm**



CODE: LAFN43048 (FOR 1 PC)
**ALUMINIUM/PLASTIC
TUBE 50 cm Ø38 mm**
(MACHINE COMES WITH 2PCS)



CODE: MPVR43047
**HANDLE WITH AIR
REGULATOR Ø38 mm**



CODE: SPPV43051
WET TOOL Ø38 mm



OPTIONAL ACCESSORIES

CODE: PMVR06680
DFS POLY KIT

