



**IPC**

BY TENNANT COMPANY

VACUUM CLEANERS - SPECIAL SOLUTIONS - FLOODED AREA EMPTYING

## GC 2/107 SUB+

POWER MAX

2400

W

WATER LIFT

2560

mmH<sub>2</sub>O

AIRFLOW

504

m<sup>3</sup>/h

TANK CAPACITY

107

l

### EXCLUSIVE FEATURES

- ▶ **NEW - 5-METER SUPER STRONG FLEX HOSE**
- ▶ **AP TUBE**
- ▶ **INNOVATIVE GASKET**
- ▶ **STRONG HOOKS**
- ▶ **INDEPENDENT MOTORS WITH LIGHT SWITCHES**
- ▶ **SEALANT FLOATER & INTEGRATED ANTIFOAM SYSTEM**
- ▶ **TIPPING TROLLEY**
- ▶ **RELIABLE CONSTRUCTION FOR INTENSIVE USE**
- ▶ **SUBMERSIBLE PUMP**



PUMP  
OUT

### MOST FREQUENTLY USE

AGRICULTURE



CONSTRUCTION



HARDWARE CUSTOMER



HEAVY INDUSTRY



AUTOMOTIVE



### INNOVATIONS



NEW BLEND  
FLEXIBLE HOSE



SUPERIOR  
AIRFLOW  
MOTOR

### SPECS



HIGH EFFICIENCY STAINLESS  
STEEL SUBMERSIBLE  
PUMP FOR INDUSTRIAL  
APPLICATION



WATER FLOW VALVE



TIPPING TROLLEY

TECHNICAL DATA

Code		GC 2/107 SUB+
PERFORMANCE		ASD015530
Usage		WET
Motor		2
Power	W	2000-2400 max
Voltage	V	220-240
Water lift	mmH <sub>2</sub> O	2560
Airflow	m <sup>3</sup> /h	504
Tank Capacity/Material	l	107/plastic (polyethylene)
Cable length	m	8,5
Sound Pressure Level (EN 60704-1; EN 60704-2-1; IEC 60335-2-69)	dB(A)	77
Pump type		Stainless Steel
Pump power	W	750
Pump capacity	l/min	400
Solids diameter for pumping out	mm	40 max
Delivery head	m	11,5
Diameter of accessories	mm	38
Dimensions (LxWxH)	mm	500x620x1110
Weight	kg	32,0

STANDARD EQUIPMENT

CODE: TBFX01277  
EXTRA STRONG FLEXIBLE  
HOSE 5 m Ø38 mm



CODE: LAFN43048 (FOR 1 PC)  
ALUMINIUM/PLASTIC  
TUBE 50 cm Ø38 mm  
(MACHINE COMES WITH 2PCS)



CODE: MPVR43047  
HANDLE WITH AIR  
REGULATOR Ø38 mm



CODE: SPPV43051  
WET TOOL Ø38 mm

