



PLANET OIL 3M

EXCLUSIVE FEATURES

- ▶ INDEPENDENT MOTORS WITH LIGHT SWITCHES
- ▶ DRAIN HOSE
- ▶ RELIABLE CONSTRUCTION FOR INTENSIVE USE
- ▶ DETACHABLE TANK AND SOLID CART
- ▶ TANGENTIAL OR METAL INLET
- ▶ DOUBLE STAGE MOTORS AND TURBINE
- ▶ BIG AND BRAKED WHEELS
- ▶ QUICK MAINTENANCE FRAMEWORK WITH DETACHABLE TANK
- ▶ SIEVE BASKET & ANTI BLOCK FLOATING SYSTEM
- ▶ ANTISKID WHEELS WITH BRAKES
- ▶ VISUAL FILLING INDICATOR
- ▶ SAFETY VALVES AND DRAIN SYSTEM
- ▶ INDUSTRIAL FRAMEWORK WITH AISI 304 WITH DETACHABLE TANK
- ▶ TANGENTIAL INLET AND CONVEYOR CONE
- ▶ VACUUM RELIEF VALVE AND FILTRATION LEVEL INDICATOR

PLANET OIL 3M

Code ASID00524

TECHNICAL DATA

Usage		WET & DRY
Number of phases		single phase
Voltage / Frequency	V	220-240/50-60
N. and type of motor		3 x 2 stages
Power	W	3600 - 3800 max
Water lift	mmH ₂ O	2795
Airflow	m ³ /h	630
Tank Capacity	l	100
Diameter of inlet	mm	60
Filtering surface	cm ²	3100+1500
Sound Pressure Level	dB(A)	76
Dimensions (LxWxH)	mm	850x650x1350
Weight	Kg	65

STANDARD EQUIPMENT

CODE: KTRI02521
FILTERING KIT
(3100 + 1500 cm²)



CODE: FTC000011
NYLON FILTER (PA 200 μ)



CODE: SECC00113
BUCKET SIEVE 40 L



OPTIONAL ACCESSORIES

Anti-oil tool kit Ø50-60 mm PMDT00447
Pre separator kit 2" y connector for tank filling KTRI05973